

GENERAL MICROPHONES

785 Group GOOSENECK PAGING MICROPHONE



A low-impedance gooseneck microphone for single zone paging. Designed for applications where ruggedness, dependability and durability are the main requirements. Microphone housing is constructed of die-cast zinc alloy to stand up to the toughest abuse and conditions. Features a recessed aluminum grille with a windscreen and durable satin-chrome finish.

- Heavy duty, three-hole mounting flange
- Extra-strength 16" steel-tubing flex arm
- SR785LN/O includes a push button switch with normally "open" switching
- SR785L is the same as SR785LN/O except without normally "open" switching
- 785L is the same as SR785LN/O except without a switch

US690 GOOSENECK MICROPHONE



US690 12" flexible gooseneck microphone's neodymium magnet structure provides up to 6 dB more sensitivity than conventional designs. The US690 terminates with an XLR-type connector and plug-in mount. Its rugged design and mic element make the US690 ideal for the most demanding applications where superb sound is required.

- 12" gooseneck
- Dynamic element
- Cardioid polar pattern
- Powerful neodymium magnet structure
- XLR termination

US600EL, US602FL PTT HAND MICROPHONE



US600EL – A hand microphone built to withstand rough usage and atmospheric extremes. Designed for maximum noise rejection in high ambient areas, it allows effective use without "close talking" techniques. An excellent choice for critical communication applications.

US602FL – A hand microphone featuring clear speech transmission in high ambient noise level environments, convenient grip-to-talk activation and noise-canceling dynamic design. Perfect for police, marine and mobile paging applications.

NC450D, 450D PTT HAND MICROPHONE



NC450D – A dynamic hand microphone with push-to-talk switch for paging. NC450D's noise-canceling design makes it particularly effective for use in noisy locations. Its excellent voice response characteristics also make it an excellent choice in quiet areas. 200 ohm impedance matches low impedance inputs.

450D – Same as NC450D except without noise-cancellation. Features a molded Cycloc housing in pebble-grain black finish and an unterminated black neoprene coil cord relieved at the housing by spring-type strain relief.

WP300S, WP300 WALL PLATE MICROPHONE



WP300S – A dynamic, omnidirectional wall plate microphone that is ideal for security monitoring, fast-food and retail outlets, warehouses and public-usage applications. Mounts onto a standard single-gang electrical box. The front plate, finished in brushed satin-chrome, includes a double-pole, double-throw switch for push-to-talk and line-shorting capabilities.

WP300 – Same as WP300S except without the double-pole, double-throw switch.

WIRED MICROPHONE ACCESSORIES

Genuine high-quality Electro-Voice wired microphone parts for direct replacement of standard equipment or optional accessories.

Shock Mounts



309A
RE20
RE27N/D
(Replacement elastic bands, PART # 71220X)



CPSM
RE90P
PC-12/XLR
PC-18/XLR



SAPL-3
PL37 (stock replacement)
RE200 (optional)

Adapters



DRC-1
Designed for PL35 (stock replacement). Also works well with N/D468.



TXA
The TXA is designed to enable the use of lavalier, headworn and other TA4F-terminated EV professional microphones in a wired configuration. Using standard phantom power through the TXA ensures the same high-quality audio performance that you expect using EV microphones over wireless systems.

Stand Adapters



311
635A
635AB
RE16
RE200
N/D468



320
RE20
RE27N/D
N/D868



323S
RE50-B
RE50N/D-B
BK-1



326
All N/Dym handhelds



SAPL-1
All PL Series handhelds



SAPL-2
PL33
RE20
RE27N/D
N/D868

Foam Windscreens

314E (black)
635A
635AB

376 (grey)
379-1 (black)
379-2 (red)
General Purpose
Fits most vocal
N/Dym Series
Cobalt Series
RE Series vocal

WSPL-1 (black)
PL Series (vocal)
RE410
RE510
RE50B
RE50N/D-B

WSPL-2 (black)
PL33
RE20
RE27N/D
N/D868

WSPL-3 (black)
PL35

WSPL-4 (black)
PL37
RE200