



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



# Floor Door, Floodtight / Gastight AW-APS

## Application

- Designed for interior and exterior applications where floodtight or gastight is required.

## Product Features

- Angle frame construction with anchors welded around the frame for casting into concrete.
- Diamond plate door panel is reinforced for a live load of 1560 pounds/sqft. (capable of holding up to 25 ft. head of water).
- Door panel overlaps frame, compressing the gasket providing a floodtight/gastight fit.
- EPDM gasket and floodtight cam locks ensure door will not leak from standing water.



## AW-APS Floor Door Specifications:

**Material:** Aluminum door & frame ; Type 316 Stainless steel hinges & hardware

**Door:** 1/4" aluminum diamond plate reinforced for live load of 1560 pounds/per sq. ft. (capable of holding up to 25 ft. head of water)

**Frame:** 3/8" aluminum with 3/16" x 1 1/2" strap anchors welded around the frame for casting into concrete

**Hinge:** Type 316 stainless steel butt hinges with tamper proof stainless steel bolts and nuts

**Gasket:** 9/16" O.D. x 1/8" I.D. EPDM gasket

**Opening Device:** Automatic hold open arm with red vinyl grip allows door to open to 90 degrees, locking door in open position and allowing for easy control when closing door panel. Stainless steel compression springs provide lift assistance.

**Standard Latch:** Type 316 stainless steel floodtight cam locks and flush floodtight handle

**Finish:** Mill finish with bituminous coating on exterior frame

## AVAILABLE SIZES (Special sizes available upon request)

FRAME I.D. SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
24 x 24	610 x 610	75	34.1
24 x 30	610 x 762	90	40.9
24 x 36	609 x 914	100	45.4
30 x 30	762 x 762	105	47.7
30 x 36	762 x 914	115	52.3
30 x 48	762 x 1220	140	63.6
36 x 36	914 x 914	130	59.1
36 x 48	914 x 1220	155	70.4

