



HIGH TEMPERATURES

Advanced Waterproofing Underlayment

Product Use: WinterGuard™ HT (High Tack, High Temperature) is an advanced waterproofing underlayment for shingle, metal, slate and tile roofs. It is specially formulated to resist high roof temperatures under metal roofs.

Product Composition and Features: WinterGuard HT has a tough, tear-resistant film on its top surface that will not scratch roofing metal applied over it. The adhesive bottom surface of WinterGuard HT is protected with a disposable silicone-coated release film, which is split longitudinally down the middle for easier application.

Applicable Standards: WinterGuard HT underlayment is manufactured on state-of-the-art, dedicated roof lines. WinterGuard HT meets or exceeds ASTM D 1970; UL 790: Classified for use as underlayment beneath Class A, B, or C fire rated shingle systems; and ICC/SBCCI ER-2024B. It can be applied beneath metal to acceptable decks with slopes of 0.5"/12" or greater and is specially designed to withstand temperatures up to 250°F.

Storage: Store WinterGuard HT rolls in their packaging in a dry, protected area at a temperature not exceeding 110°F.

Low Slope Shingle, Metal, Slate or Tile Application: WinterGuard HT can be applied under these roofing materials to provide protection against the infiltration of wind-driven rain on low slope applications.

Technical Data:	Description	HT film (short)	HT film
	Roll area (sq. ft.)	97.5	195
	Roll length (ft.)	32.5	65
	Roll width (ft.)	3	3

750 East Swedesford Rd.
P.O. Box 860 • Valley Forge, PA 19482
610-341-7000 • 800-233-8990 Sales Support Group

West Region

6400 Stevenson Blvd., Fremont, CA 94538
800-955-0811 • 510-438-0271 fax

South Region

5525 MacArthur Blvd., Suite 680, Irving, TX 75038
800-333-ROOF (7663) • 972-580-5645 fax

North Region

Riverbridge Industrial Center
800 W. Front Street, Chester, PA 19013
866-297-ROOF (7663) • 610-874-6170 fax

www.certainteed.com

