CertainTeed® Ridge Vent

12" Unfiltered Shingle-Over Ridge Vent



a New Level of Performance

CertainTeed® Ridge Vent installs on the peak of the roof, allowing exhaust ventilation along the entire ridge, end-to-end. With a 12" width, matching shingles can be installed over the vent, allowing the vent to appear almost invisible from the ground. Intake vents must be installed to provide proper airflow. CertainTeed Ridge Vents combined with sufficient intake vents, such as CertainTeed Intake Vent, are the most efficient and effective systems you can install.



CertainTeed® Ridge Vent

The low-profile, shingle-over look of CertainTeed® Ridge Vent creates a clean, uncluttered roofline.



Imprinted slot guides for - proper slot width

Highest quality co-polymer remains sturdy, nailable and flexible in all climates

Reinforced ribs for greater stability and rigidity

Built-in ventilating —— end plug seals the end

Cap shingles install — easily making the vent virtually invisible

 Nail holes located at 16" and 24" centers

Nail bosses, reinforced nail holes designated to prevent over nailing

High gloss nailing lines for accurate, fast cap shingle nailing

Air slots have 18" sq. free vent area per linear ft.

External wind baffle creates low air pressure and helps pull air out of the attic

Features

- Designed with an external baffle to deflect wind and weather over the vent to help protect the attic from rain and snow infiltration. The external baffle creates low pressure over the vent openings to "pull" air from the attic
- 18" sq. of net free area per linear foot
- CertainTeed Ridge Vent is pre-formed to a 4/12 pitch, and fits pitches from 3/12 to 16/12
- Limited Lifetime Warranty and 5-Year SureStart™ Protection
- CertainTeed Ridge Vent comes with thirty 3-inch ring shank, galvanized roofing nails bagged and taped to each 4-foot piece inside the carton
- Ten 4' pieces per box / Weight: 24 lbs. / Part #95984 Model #VVPN / Color: Black
- · Includes nails

Benefits

- Works year-round to ventilate the attic
- Provides evenly distributed ventilation along the entire underside of the roof
- Slim design for visual appeal
- Provides a higher volume of airflow per square foot of attic area than any other fixed-vent system
- Design maximizes airflow across the entire underside of roof sheathing
- Changes in wind direction have no significant effect on vent performance
- Wind driven rain resistant to 110 MPH

VenturiVent Plus is Manufactured for CertainTeed Corporation by Air Vent, Inc., Orrick, MO.









ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com

http://blog.certainteed.com

CertainTeed Corporation P.O. Box 860 Valley Forge, PA 19482

Professional: 800-233-8990 Consumer: 800-782-8777

© 10/13 CertainTeed Corporation, Printed in the U.S.A. Code No. 20-20-3455

