

## DTP SYSTEMS

**DTP T HWP 332 D****Long Distance Two Input DTP Transmitter for HDMI  
- Decora® Wallplate**

The Extron DTP T HWP 332 D is a two input Decora®-style transmitter for sending HDMI, audio, and control up to 330 feet (100 meters) over a shielded CATx cable to Extron DTP 330-enabled products. It is HDCP compliant and provides two HDMI inputs, both with independent analog stereo audio connections. The DTP T HWP 332 D supports computer video up to 1920x1200, including HDTV 1080p/60 and 2K. The transmitter also offers many integrator-friendly features such as EDID Minder®, auto-switching between inputs, remote power capability, and bidirectional RS-232 and IR pass-through for remote AV device control. The wall-mountable design of the DTP T HWP 332 D provides the convenience of placing input connections precisely where they are needed.

**FEATURES**

- Transmits HDMI, control, and analog audio up to 330 feet (100 meters) over a shielded CATx cable
- Two HDMI inputs
- Auto-switching between inputs
- Supports computer video up to 1920x1200, including HDTV 1080p/60 and 2K
- Extron XTP DTP 24 shielded twisted pair cable is strongly recommended for optimal performance
- Independent analog audio inputs
- Bidirectional RS-232 and IR pass-through for AV device control
- Remote power capability
- HDCP compliant
- EDID Minder® automatically manages EDID communication between connected devices
- Supports EDID and HDCP transmission
- RS-232 control port
- Contact closure control port
- RJ-45 signal and link LED indicators for DTP port

**NOW SHIPPING**

Model	Version Description	Part Number
DTP T HWP 332 D	Two Input Decora Transmitter - Black .....	60-1365-52
DTP T HWP 332 D	Two Input Decora Transmitter - White .....	60-1365-53

**DTP T UWP 332 D****Long Distance Two Input DTP Transmitter for HDMI and VGA  
- Decora® Wallplate**

The Extron DTP T UWP 332 D is a two input Decora®-style transmitter for sending HDMI or analog video, audio, and control up to 330 feet (100 meters) over a shielded CATx cable to Extron DTP 330-enabled products. The transmitter provides one HDMI input and one VGA input, both with independent analog stereo audio connections. The DTP T UWP 332 D supports computer video up to 1920x1200, including 1080p/60 and 2K. It digitizes incoming analog video for reliable display on a variety of output devices. Integrator-friendly features include EDID Minder®, auto-switching between inputs, remote power capability, and bidirectional RS-232 and IR pass-through for remote AV device control. The wall-mountable design of the DTP T UWP 332 D provides the convenience of placing input connections precisely where they are needed.

**FEATURES**

- Transmits HDMI or analog video, control, and analog audio up to 330 feet (100 meters) over a shielded CATx cable
- One HDMI input and one VGA input
- Auto-switching between inputs
- Supports computer video up to 1920x1200, including HDTV 1080p/60 and 2K
- Extron XTP DTP 24 shielded twisted pair cable is strongly recommended for optimal performance
- Independent analog audio inputs
- Bidirectional RS-232 and IR pass-through for AV device control
- Remote power capability
- HDCP compliant
- EDID Minder® automatically manages EDID communication between connected devices
- Supports EDID and HDCP transmission
- RS-232 control port
- Contact closure control port
- RJ-45 signal and link LED indicators for DTP port

**NOW SHIPPING**

Model	Version Description	Part Number
DTP T UWP 332 D	Two Input Decora Transmitter - Black .....	60-1366-52
DTP T UWP 332 D	Two Input Decora Transmitter - White .....	60-1366-53

For updated product availability, go to [www.extron.com](http://www.extron.com)