CertainTeed® Ridge Vent

9" Class A Fire Rated Filtered Shingle-Over Ridge Vent



With the same features as CertainTeed® Ridge Vent Filtered,
this high-performance ridge vent is 9" wide so it can
be used with many enhanced ridge and cap shingles.
CertainTeed Ridge Vents combined with sufficient
intake vents, such as CertainTeed Intake Vent, are the
most efficient and effective systems you can install.



CertainTeed® Ridge Vent

Rated for Class A roof decks in accordance with UL standards.



Imprinted slot guides for _
proper slot width

Highest quality co-polymer remains sturdy, nailable and flexible in all climates

Reinforced ribs for greater stability and rigidity

Built-in ventilating —— end plug seals the end

Cap shingles install — easily making the vent virtually invisible

Nail holes located at 16" and 24" centers

Nail bosses, reinforced nail holes designated to prevent over nailing

Weather filter provides advanced protection from rain, snow, dust and insect intrusion

High gloss nailing lines for accurate, fast cap shingle nailing

Air slots have 16" sq. free vent area per linear ft.

External wind baffle creates low air pressure and helps pull air out of the attic

Features

- Designed with an external baffle to deflect wind and weather over the vent to help protect the attic from rain and snow infiltration. The external baffle creates low pressure over the vent openings to "pull" air from the attic
- Internal weather filter provides a more complete barrier to help protect the attic from wind-driven rain, snow, dust and insects
- Easy installation has pre-printed slot guides for truss or ridge pole construction. Pre-drilled nail holes are designed to assure proper nailing
- 16" sq. of net free area per linear foot
- CertainTeed Ridge Vent is pre-formed to a 4/12 pitch, and fits pitches from 3/12 to 12/12
- Limited Lifetime Warranty and 5-Year SureStart™ Protection
- Ten 4' pieces per box / Weight: 19 lbs. / Part #95985
 Model #CLASH9CC / Color: Charcoal

Benefits

- Works year-round to ventilate the attic
- Provides evenly distributed ventilation along the entire underside of the roof
- Slim design for visual appeal
- Provides a higher volume of airflow per square foot of attic area than any other fixed-vent system
- Design maximizes airflow across the entire underside of roof sheathing
- Changes in wind direction have no significant effect on vent performance





ShingleVent II 9-A is Manufactured for CertainTeed Corporation by Air Vent, Inc., Orrick, MO.





ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com

http://blog.certainteed.com

CertainTeed Corporation P.O. Box 860 Valley Forge, PA 19482

Professional: 800-233-8990 Consumer: 800-782-8777

© 10/13 CertainTeed Corporation, Printed in the U.S.A. Code No. 20-20-3462

