

LFII

Dry Type Recessed Pendant

- 3 mm bulb type
- Where sprinklers are required on dry pipe systems that are exposed to freezing temperatures, or where sprinklers are seasonally drained to avoid freezing
- Offer the features of non-water filled pipe in addition to not having to increase the number of design sprinklers (hydraulic design area) for systems designed to NFPA 13, 13D, or 13R
- Intended for use in the following residential sprinkler systems scenarios:
 - one/two-family dwellings and mobile homes per NFPA 13D,
 - residential occupancies up to and including four stories in height per NFPA 13R
 - the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.9 (70,6)
THREAD SIZE	1" NPT or ISO 7-R1
APPROVALS	UL
TEMPERATURE	155°F/68°C, 175°F/79°C (wet pipe only)
ESCUTCHEON FINISH	Signal White, Chrome Plated, Natural Brass
SPRINKLER FINISH	Signal White, Chrome Plated, Natural Brass
SIN	TY2235
TECH DATA	TFP460



Sprinkler Wrench



Dry Type Recessed Horizontal Sidewall

- 3 mm bulb type
- Where sprinklers are required on dry pipe systems that are exposed to freezing temperatures, or where sprinklers are seasonally drained to avoid freezing
- Offer the features of non-water filled pipe in addition to not having to increase the number of design sprinklers (hydraulic design area) for systems designed to NFPA 13, 13D, or 13R
- Intended for use in the following residential sprinkler systems scenarios:
 - one/two-family dwellings and mobile homes per NFPA 13D,
 - residential occupancies up to and including four stories in height per NFPA 13R
 - the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.4 (63,4)
THREAD SIZE	1" NPT or ISO 7-R1
APPROVALS	UL
TEMPERATURE	155°F/68°C
ESCUTCHEON FINISH	Signal White, Chrome Plated, Natural Brass
SPRINKLER FINISH	Signal White, Chrome Plated, Natural Brass
SIN	TY2335
TECH DATA	TFP461



Sprinkler Wrenches

