

### DS-C

#### Concealed Pendent

- Standard coverage
- All hazard (standard response)
- Light hazard/ordinary hazard (quick response)
- 3 mm and 5 mm bulb
- Lengths to 48" (1220 mm)
- Designed for use in applications where sprinklers and/or connecting piping may be exposed to freezing conditions, or the sprinkler system is seasonally drained
- Special assembly provides a seal at the main pipe to prevent water from entering the sprinkler assembly until the sprinkler operates

<b>K FACTOR</b>	K=5.6 (80,6)
<b>INLET THREAD CONNECTION</b>	1" NPT (Standard Order) ISO 7-R1
<b>APPROVALS</b>	UL, C-UL, NYC
<b>TEMPERATURE</b>	155°F/68°C - Sprinkler 139°F/59°C - Cover Plate, 200°F/93°C - Sprinkler 165°F/74°C - Cover Plate
<b>COVER PLATE FINISH</b>	Grey White, Brass, Pure White, Signal White, Jet Black, Chrome, Custom
<b>SIN</b>	TY3535, TY3555
<b>TECH DATA</b>	TFP515



Sprinkler Wrench  
RPI

### DS-ECC

#### Extended Coverage Concealed Pendent

- EC light hazard/EC ordinary hazard
- 3 mm bulb
- Lengths to 48" (1220 mm)
- Designed for use in applications where sprinklers and/or connecting piping may be exposed to freezing conditions, or the sprinkler system is seasonally drained
- Special assembly provides a seal at the main pipe to prevent water from entering the sprinkler assembly until the sprinkler operates

<b>K FACTOR</b>	K=5.6 (80,6)
<b>INLET THREAD CONNECTION</b>	1" NPT (Standard Order) ISO 7-R1
<b>APPROVALS</b>	UL, C-UL, NYC
<b>TEMPERATURE</b>	155°F/68°C - Sprinkler 139°F/59°C - Cover Plate, 200°F/93°C - Sprinkler 165°F/74°C - Cover Plate
<b>COVER PLATE FINISH</b>	Grey White, Brass, Pure White, Signal White, Jet Black, Chrome, Custom
<b>SIN</b>	TY3539
<b>TECH DATA</b>	TFP518



Sprinkler Wrench  
RPI