# AUTOMATIC SPRINKLERS RAPID RESPONSE™ SPRINKLERS

#### 

## LFII

### **Domed Plate Concealed Pendent**

- 3 mm bulb type
- Can be used for horizontal and sloped ceilings
- Cover plate conceals sprinkler components above the ceiling
- Intended for use in the following scenarios:
  wet and dry pipe residential sprinkler
  - systems for one/two-family dwellings and mobile homes per NFPA 13D
  - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
  - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.9 (70,6)
THREAD SIZE	<sup>1</sup> ⁄2" NPT
APPROVALS	UL, C-UL, NYC
TEMPERATURE	155°F/68°C - Sprinkler
	139°F/59°C - Cover Plate
ESCUTCHEON	Style 20
COVER PLATE FINISH	Pure White, Signal White, Chrome, Custom
SIN	TY2234
TECH DATA	TFP450



Sprinkler Wrench W-TYPE 7



## Flush Pendent

#### • Solder type

- Intended for use in the following scenarios:
  - wet and dry pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
  - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
  - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13
- Approved for special applications with beamed ceilings

#### K=4.2 (60,5) **K FACTOR** <sup>1</sup>/2" NPT THREAD SIZE UL, C-UL APPROVALS 162°F/72°C TEMPERATURE ESCUTCHEON FINISH Signal White, Jet Black, Chrome Plated, **Antique Brass** Signal White, Jet Black, SPRINKLER FINISH Chrome Plated, **Antique Brass** TY2284 SIN TFP420 **TECH DATA**





#### Flush Horizontal Sidewall

- Solder type
- Intended for use in the following scenarios:
  - wet pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
  - wet pipe residential occupancies up to and including four stories in height per NFPA 13R
  - wet pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.2 (60,5)
THREAD SIZE	<sup>1</sup> ⁄2" NPT
APPROVALS	UL, C-UL
TEMPERATURE	162°F/72°C
	Signal White, Chrome, Jet Black
SPRINKLER FINISH	Signal White, Chrome, Jet Black
SIN	TY2384
TECH DATA	TFP425





30