DRY SPRINKLERS

DS-1

Pendent, Upright & Horizontal Sidewall

- Standard coverage
- All hazards (light hazards, horizontal sidewall)
- 5 mm bulb
- Lengths up to 48" (1220 mm)
- Designed for use in applications where sprinklers and/or connecting piping may be exposed to freezing conditions, or the sprinkler system is seasonally drained
- Special assembly provides a seal at the main pipe to prevent water from entering the assembly until the sprinkler operates
- Designed for use in applications requiring dry sprinklers, or where building construction or aesthetic considerations make the installation of dry horizontal sidewall sprinklers more desirable than the dry pendent type

K FACTOR	K=5.6 (80,6)
INLET THREAD CONNECTION	1" NPT (Standard Order) ISO 7-R1
APPROVALS	Upright=UL, C-UL, FM, NYC • Pendent & Horizontal Sidewall= UL, C-UL, FM, NYC, LPCB
TEMPERATURE	135°F/57°C, 155°F/68°C, 175°F/79°C, 200°F/93°C, 286°F/141°C, 360°F/182°C
ESCUTCHEON FINISH	Signal White, Chrome Plated, Brass Plated
SPRINKLER FINISH	Natural Brass, Chrome Plated, Signal White
SIN	TY3255, TY3155, TY3355
TECH DATA	TFP500

Sprinkler Wrench
W-TYPE 7

Pendent, Upright & Horizontal Sidewall

- Light hazard/Ordinary hazard
- 3 mm bulb
- Lengths to 48" (1220 mm)
- Designed for use in applications where sprinklers and/or connecting piping may be exposed to freezing conditions, or the sprinkler system is seasonally drained
- Special assembly provides a seal at the main pipe to prevent water from entering the assembly until the sprinkler operates
- Designed for use in applications requiring dry sprinklers, or where building construction or aesthetic considerations make the installation of dry horizontal sidewall sprinklers more desirable than the dry pendent type

K FACTOR	K=5.6 (80,6)
INLET THREAD CONNECTION	¾" or 1" NPT (Std. Order) ISO 7-R1
APPROVALS	¾"= UL, C-UL • 1"= UL, C-UL, FM, NYC
TEMPERATURE	135°F/57°C, 155°F/68°C, 175°F/79°C, 200°F/93°C, 286°F/141°C
ESCUTCHEON FINISH	Signal White, Chrome Plated, Brass Plated
SPRINKLER FINISH	Natural Brass, Chrome Plated, Signal White
SIN	TY3235, TY3135, TY3335 TY3935, TY3735
TECH DATA	TFP510

Sprinkler Wrench
W-TYPE 7

Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.