

LFII

Horizontal & Recessed Horizontal Sidewall

- 3 mm bulb type
- Intended for use in the following scenarios:
 - wet and dry pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
 - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.2 (60,5)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL, NYC, NSF
TEMPERATURE	155°F/68°C, 175°F/79°C
ESCUTCHEON	Style 20
SPRINKLER FINISH	Pure White, Signal White, Chrome Plated, Natural Brass
SIN	TY1334
TECH DATA	TFP410



Sprinkler Wrenches



Flat Plate Concealed Pendent

- Solder type
- Provides 1/4" inch (6 mm) vertical adjustment. This adjustment provides flexibility when cutting fixed sprinkler drops.
- Cover plate conceals sprinkler components above the ceiling
- Intended for use in the following scenarios:
 - wet and dry pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
 - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.9 (70,6)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL, NYC, NSF
TEMPERATURE	160°F/71°C - Sprinkler 139°F/59°C - Cover Plate
COVER PLATE FINISH	Ivory, Beige, Pure White, Signal White, Grey White, Brown, Black, Brushed Brass, Brushed Chrome, Custom
SIN	TY3596
TECH DATA	TFP442



Sprinkler Wrench



Flat Plate Concealed Pendent

- Solder type
- Can be used for horizontal and sloped ceilings
- Provides 1/2" inch (13 mm) vertical adjustment. This adjustment provides flexibility when cutting fixed sprinkler drops.
- Cover plate conceals sprinkler components above the ceiling
- Intended for use in the following scenarios:
 - wet and dry pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
 - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.9 (70,6)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL
TEMPERATURE	160°F/71°C - Sprinkler 139°F/59°C - Cover Plate
COVER PLATE FINISH	Ivory, Beige, Pure White, Signal White, Grey White, Brown, Black, Brushed Brass, Brushed Chrome, Custom
SIN	TY2524
TECH DATA	TFP443



Sprinkler Wrench



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.