

EQ700

True Day/Night Box Camera



Features

- Ultra resolution of over 720 horizontal TV lines for astounding image quality
- Exview HAD II sensor delivers amazing ultra high sensitivity of .05 lux – very low light sensitivity without DSS low light boost - Zero Ghosting guaranteed
- Digital Wide Dynamic Range expansion to deliver properly exposed images despite unbalanced lighting in the scene
- Provides 2D-Noise Reduction to improve picture clarity while enabling DVRs to improve disk storage utilization
- Full suite of OSD menu options controlled from the built-in joystick
- Digital Wide Dynamic Range expansion to deliver properly exposed images despite bright light sources, deep shadows and/or unbalanced lighting in the same scene

720+
Ultra Series

720+
TVL

True D/N

POWER
12VDC/
24VAC

OSD

DIGITAL WDR


2D
Noise
Reduction

HSBLC

Specifications

| Part Number | EQ700 |
|-------------------------------|--|
| Pickup Device | 1/3" Sony Exview HAD II 960H High Sensitivity Interline CCD |
| Video Format | NTSC or Pal |
| Picture Elements | 1020 x 508 (NTSC) 1020 x 508 (NTSC) |
| Effective Pixels (NTSC PAL) | 976 x 494 (NTSC) 976 x 582 (PAL) |
| Scanning System | 2:1 Interlace |
| Horizontal Resolution | 720+ TVL |
| Sensitivity | Color ~ 0.001 lux, B/W ~ 0.0001 Lux/F=1.0 |
| S/N Ratio | Over 50dB (AGC off) |
| Electronic Shutter | 1/60s~1/100,000s |
| Video Output | BNC 1.0Vp-p 75Ω |
| Gamma Correction | 0.45 |
| Lens Type | C/CS Mount (lens sold sep) |
| Lens Options | Fixed |
| BLC | OFF/BLC/HSBLC Selectable |
| Gain Control | Low light auto, bright light auto, manual selectable |
| White Balance | ATW, One Push, User1, User2, Anti-Crawl, Manual, Push Lock |
| Sync Mode | Internal Sync |
| Day/Night | True D/N with motorized IR cut filter; Choose Color, B/W, Auto |
| OSD Menu | Multiple Functions |
| OSD Languages | English, Spanish, French, Chinese, German, Japanese, Portuguese, Russian |
| Digital Noise Reduction | 2D On/Off (Level adjustable) |
| ATR | On/Off (3 levels each adjustable for luminance and contrast) |
| Wide Dynamic Range | On/Off (3 levels each adjustable for luminance and contrast) |
| Mirror | Off/On |
| Motion Detection | Off/On for 4 selectable zones (On screen indication on alarm) |
| Privacy Mask | Off/On for 4 selectable zones |
| Environmental | Indoor/Sep Housing |
| Power Source | 12VDC/24VAC |
| Power Consumption | 12VDC: 180mA (2.16W) max 24VAC: 2.9W max |
| Operating Temp | 14°F~122°F -10°C~50°C |
| Humidity | Less than 80% non-condensing |
| Dimensions (in mm) | 2.28 x 2.28 x 4.765" 58 x 58 x 121mm |
| Weight (lbs gm) | 0.88lbs 400g |
| Certifications | CE/FCC |

Dimensions: mm/in



Ordering Info

EQ700: Day/Night Box Camera, 720+ TVL

