
## AUTOMATIC SPRINKLERS SPECIAL PURPOSE SPRINKLERS

## ATTIC

## BB (Back-to-Back), SD (Single Directional), HIP, & AP (Attic Plus)

- "Specific Application Sprinklers for Protecting Attics"
- 3 mm bulb or solder type
- Wet or dry pipe systems
- Provides a tested method of protecting an attic
- Provides a specific cost advantage by reducing the amount of piping required
- Cover attics to 60'-0" wide with a single line of piping, eliminating the need for as many as five branch lines
- Saves up to 80% of the piping that would be required with standard sprinklers while providing a higher level of protection

K FACTOR	K=4.2 (60,5), K=5.6 (80,60), K=8.0 (115,2)
THREAD SIZE	½" NPT ¾" NPT
APPROVALS	UL, ULC,
TEMPERATURE	200°F/93°C, 212°F/100°C
SPRINKLER FINISH	Natural Brass
SIN	TY4180, TY4181, TY4182 TY3180, TY3181, TY3182 TY2180, TY2181, TY2182 TY3183, TY3184, TY3185 TY3187, TY3190, TY2190
TECH DATA	TFP610



**Back-To-Back Application** 

**Hip Application** 

**Single Directional** 

Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.

**Back-To-Back** 

Hip