

Welding Equipment

#WEC-13





Butt Fusion Shop • Hydraulic Trench • Socket Fusion • Electrofusion • IR/Beadless High Purity

Another Corrosion Problem Solved.™



www.asahi-america.com

Welding Equipment Catalog #WEC-13

Butt Fusion Shop Welders

Miniplast: Shop 4, Maxiplast: Shop 6	Page	3
Shop 12 Manual (W2500), Shop 12 Hydraulic.(W4002)	Page	4
Halar® Bench 6 (W900)	Page	5

Hydraulic Trench Machines

Trench 6 (W4400), Trench 12 (W4900)	. Page	6
Trench 20 (W5500)	. Page	7

Socket Fusion Welders

Bench Socket 4 (W3500)Page	8
Ritmo Hand Held Socket 2, Widos Weld-it® Hand Socket Page	9

Electrofusion Welder

The Polymatic, XTR400Page 1	10
Hot Air Welder, Extrusion Star Gun Page 1	11

I/R High Purity Welders

SP 110-S: Fully Automated Welding IR Fusion	Page 12
SP 250-S: Fully Automated Welding IR Fusion	
SP 315-S: Fully Automated Welding IR Fusion	
Power Transformer	Page 13

Beadless Welder

SP 110-B: Fully Automated Beadless Fusion	Page 14
HPF Portable Beadless Fusion	Page 15

Accessories

Rotational Scraper 110 & 225, Pipe Beveller SME-1	. Page 16
Balloons and Heater Bushings	Page 17
Electrofusion Couplings	. Page 18

Piping Systems

Industrial Piping Systems	Page 20
High Purity Piping Systems	
Double Containment Piping Systems	

2 ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Miniplast: Shop 4

Compact Manual Butt Fusion



Features

- Horizontal and vertical adjustment
- Compact design
- Ability to make angle welds and miter joints
- Built-in force gauge
- Removable from base for field operation
- 1x2, 2x3 Poly-Flo® inserts

Purchase Part Number 5730000 9730000 **Rental Part Number**



Size Range	20mm - 110mm (1/2" - 4")
Piping	Single & Double Wall
Materials	PE, PP, PVDF
Power	110v
Dimensions	21"x27"x19"
Weight	100 lbs.
Shipping Dimensions	48"x40"x23"
Shipping Weight	150 lbs.

Options

- IPS Inserts 1/2" 3"
- 1x3 annular heating element
- 2x4 annular heating element
- Electric planer

Maxiplast: Shop 6

Manual Butt Fusion



Features

- Horizontal and vertical adjustment
- Compact design
- Ability to make angle welds and miter joints
- Electric planer standard
- Built-in force gauge
- Removable from base for field operation
- 1x2, 2x3, 4x6 Poly-Flo[®] inserts

Purchase Part Number 5622000 **Rental Part Number** 9622000



Size Range	50mm - 160mm (1-1/2" - 6")
Piping	Single & Double Wall
Materials	PE, PP, PVDF
Power	110v
Dimensions	36"x25"x38"
Weight	250 lbs.
Shipping Dimensions	48"x40"x35"
Shipping Weight	300 lbs.

Options

- 125mm, 140mm inserts
- 3 x 6 annular mirror
- IPS inserts 1-1/2" 6"

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com



Shop 12 Manual (W2500)

Manual Butt Fusion



Features

- Suitable for sanitary installations & waste pipes
- Built-in force gauge
- Ideal for shop operation
- Horizontal and vertical adjustment
- 4x6 Poly-Flo[®] inserts

Shop 12 Hydraulic (W4002)

Purchase Part Number 5790000 Rental Part Number 9790000

Hydraulic Butt Fusion



Size Range Piping **Materials** Power

Dimensions Weight **Shipping Dimensions** Shipping Weight

90mm - 315mm (3" - 12") Single & Double Wall PE, PP, PVDF 220v / 30 Amp / 3 ph

> 50"x42"x50" 800 lbs 62"x55"x68" 1100 lbs

Butt

Size Range Piping **Materials Power**

50mm - 315mm (1-1/2" - 12") Single & Double Wall PE, PP, PVDF 110v

Dimensions Weight **Shipping Dimensions Shipping Weight**

38"x27"x41" 475 lbs. 48"x40"x45" 625 lbs.

Options

- IPS inserts 3" 10"
- 3x6, 4x8, 6x10, 8x12 annular heating element

Features

- Electro-hydraulic force control
- Robust frame for shop installations
- Designed for SDR11 thick wall pressure pipe
- Suitable for Chem Proline[®], Proline[®] & Duo Pro[®]
- Ideal for shop operation




Purchase Part Number 5722000 9722000 **Rental Part Number**



Halar® Bench 6 (W900)

Manual Butt Fusion for Halar® (E-CTFE)



Purchase Part Number 5773000 Rental Part Number 9773000



Size Range	50mm - 160mm (1-1/2" - 6")
Piping	Single Wall
Materials	Halar® (E-CTFE)
Power	110v
Dimensions	32"x21"x36"
Weight	180 lbs.
Shipping Dimensions	33"23"x36"
Shipping Weight	180 lbs.


Features

- High temp heating plate for Halar[®] welds
- Lever action for quick change over time
- Thin master clamps for keeping tight fabrication dimensions
- Built-in force gauge
- Ideal for shop operation



Trench 6 (W4400)

Compact Trench Butt Fusion



Purchase Part Number 5792000 **Rental Part Number** 9792000



Size Range Piping **Materials Power** Dimensions

Options

Weight **Shipping Dimensions Shipping Weight**

• IPS inserts 1-1/2" - 4"

50mm - 160mm (1-1/2" - 6") Single & Double Wall PE, PP, PVDF 230v / 20 Amp

> 25"x14"x14" 50 lbs. 33"x33"x26" 320 lbs.

Features

- Compact design
- Rugged frame for industrial applications
- Adjustable speed to control change over time
- Adjustable heating element temperatures
- Powerful planer with safety shut-off switch
- Lever actuated operation
- Vertical or horizontal welds
- 1x2, 2x3, 4x6 Poly-Flo[®] inserts

Trench 12 (W4900)

Trench Butt Fusion



Features

6

- Compact design
- Rugged frame for industrial applications
- Adjustable speed to control change over time
- Adjustable heating element temperatures
- Powerful planer with safety shut-off switch
- Lever actuated operation
- Vertical or horizontal welds

Purchase Part Number 5793000 9793000 **Rental Part Number**

> 90mm - 315mm (3" - 12") Single & Double Wall PE, PP, PVDF 230v / 20 Amp

Dimensions Weight **Shipping Dimensions Shipping Weight**

Options

Size Range

Piping

Power

Materials

- IPS inserts 3" 10"
- Built-in force gauge

ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Butt

34"x22"x22"

40"x48"24"

114 lbs.

900 lbs.

Trench 20 (W5500)

Trench Butt Fusion



Features

- Compact design
- Rugged frame for industrial applications
- Adjustable speed to control change over time
- Adjustable heating element temperatures
- Powerful planer with safety shut-off switch
- Lever actuated operation
- Vertical or horizontal welds

Purchase Part Number 5676000 Rental Part Number 9676000



Size Range Piping Materials Power

Dimensions Weight **Shipping Dimensions Shipping Weight**

200mm - 500mm (8" - 20") Single & Double Wall PE, PP, PVDF 230v / 3ph / 30 Amp

48"x38"x38" 300 lbs. 54"x50"x69 1545 lbs

Options

• IPS inserts 8" - 18"

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.



Bench Socket 4 (W3500)*

Bench Top Socket Welding Machine



Purchase Part Number 5711000Rental Part Number9711000



Size Range	20mm - 110mm (1/2" - 4")
Piping	Single Wall
Materials	PE, PP, PVDF
Power	110v
Dimensions Weight Shipping Dimensions Shipping Weight	28"x20"x15" 98 lbs. 32"x47"x28" 240 lbs.

Features

Smooth operation with rack-and-pinion mechanism

- Heating element is built into the machine
- Adjustable depth stop
- Ideal for shop operation
- Equipped with bevelling tool

* Notes

Heater inserts included with purchase Heater inserts must be purchased for rental machines

Options

• Heater bushings (see page 17)

See page 17 for list of heater bushings and sizes

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

8 ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Ritmo Hand Held Socket 2*

Hand Held Socket Fusion Tool



Rental Part Number 9687001

Purchase Part Number 5687001

Size Range Piping **Materials** Power

Dimensions Weight

20mm - 63mm (1/2" - 2") Single Wall PE, PP, PVDF 110v

> 18"x14"x5-1/2" 15 lbs.

Features

- Light weight durable hand tool
- Convenient table clamp and stand

Options

- Beveller tool (SME-1) (see page 16)
- Heater bushings (see page 17)

* Note

Heater inserts not included with purchase or rental

Widos Weld-it[®] Hand Socket* Part Number 5687002

Hand Held Socket Fusion Tool



Features

- Lightweight, durable hand tool
- Convenient table clamp
- Adjustable heating element, with digital indicator
- Ideal for shop or field operation

Size Range	20mm - 63mm (1/2" - 2")
Piping	Single Wall
Materials	PE, PP, PVDF
Power	110v
Dimensions	15"x6"
Weight	3.75 lbs.
Weight w/case	15 lbs.

Options

۱ ۱

- Beveller tool (SME-1) (see page 16)
- Heater bushings (see page 17)

* Note

Heater inserts not included with purchase or rental

See page 17 for list of heater bushings and sizes

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com



Polymatic*

Electrofusion Welder

Features

- Parameters are set using a bar code
- Safe and reliable fusion
- Tough thermoplastic housing that resists damage due to moisture
- Ideal for shop or field operation
- 25-110mm scrapping tool

Purchase Part Number 5830000 Rental Part Number 9830000



Size Range	All electrofusion fittings up to 48 volt
Piping	Single Wall
Materials	PE, PP
Power	110v
Dimensions	21"x27"x19"
Weight	40 lbs.
Shipping Dimens	sions 21"x27"x19"
Shipping Weight	150 lbs.

Options

- 90-225mm scrapping tool
- 220V tool available
- Requires couplings (see page 18)

Scraper is included, must specify size (see page 16)

XTR400* Purchase Part Number 5830001 Rental Part Number 9830001

* Note

Electrofusion Welder



20mm - 400mm (1/2" - 16") Size Range Single Wall Piping PE, PP **Materials** 110v, 4,000w Power 21"x17.5"x9" Dimensions 50 lbs. Weight 21"x17.5"x9" **Shipping Dimensions**

Features

- Barcode gun reads fitting label
- USB input for downloading up to 500
- complete welds
- Large graphic display with easy manual input
- Alligator pins eliminates electrical connection from slipping
- 20-400mm scrapping tool * Note
 - Scraper is included, must specify size (see page 16)

Shipping Weight

• Requires couplings (see page 18)

Options

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

10 ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com



50 lbs.

Hot Air Welder*

Manual Hand Held Bead Welding Tool



Features

- Built in motor with air cooler
- Adjustable from 20 600°C (68-1112°F)
- Ideal for light fabrication
- Supplied with spreed tacking tip 4mm

Purchase Part Number 5638000 **Rental Part Number** 9638000



21"x27"x19"

21"x27"x19"

5 lbs.

5 lbs.

3mm-4mm Size Range PFA, PVC, PE, PP, PVDF, E-CTFE **Materials** 110v Power

Dimensions Weight **Shipping Dimensions Shipping Weight**

Options

Various sizes and style tips available

Extrusion Star Gun

Manual Hand Held Extrusion Welding Tool



Rod Size Range	3-5mm (1/8" - 3/16")
Materials	PE, PP, PVDF, E-CTFE
Power	230v
Dimensions	20" x 12" x 4-1/2
Weight	50 lbs.
Shipping Dimensions	24"x13"x 8"
Shipping Weight	60 lbs.

Features

- Self contained built in motor with
- w/variable welding speed
- Ideal for light* industrial fabrication of PP,PE & PVDF

* Note

Consult factory for a seperate unit (9650000) also available for heavy fabrication

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409



Purchase Part Number 5640000 Rental Part Number 9640000



SP 110-S

Fully Automated IR Butt Welding Tool



Features

- Automated planing depth feature
- Automated fusion process
- Internal validation program
- Printer and cleanroom labels
- 110 to 230 VAC power converter
- Ideal for shop operation

Purchase Part Number 5861001 Rental Part Number 9861001



Size Range Piping Materials

Power

Dimensions Weight Shipping Dimensions Shipping Weight 20mm - 110mm (1/2" - 4") Single Wall PP, PPn, PVDF, E-CTFE Plug-110v Tool-230v / 15 Amp

> 29-9/16x35-3/8x25 198 lbs. 61"x39"x40" 670 lbs.

Options

- PFA capable tool
- SP 110-S operator card

SP 250-S

Fully Automated IR Butt Welding Tool



Purchase Part Number 5869001 Rental Part Number 9869001



110mm - 250mm (4" - 10") Single Wall PP, PVDF 208v / 3ph / 30 Amp

Dimensions Weight Shipping Dimensions Shipping Weight

Size Range

Materials

Piping

Power


36"x56"x58" 1635 lbs. 37"x56"x58" 1960 lbs.

Features

- Automated planing depth feature
- Automated fusion process
- Internal validation program
- Printer and cleanroom labels
- Ideal for shop operation

Options

- SP 250-S operator card
- 208 to 400 power converter (see page 13)



SP 315-S

Fully Automated IR Butt Welding Tool



Features

- Automated planing depth feature
- Automated fusion process
- Internal validation program
- Printer and cleanroom labels
- Ideal for shop operation

Purchase Part Number 5869315 **Rental Part Number** 9869315



Size Range Piping **Materials** Power

Dimensions Weight Shipping Dimensions Shipping Weight

Single Wall PP, PVDF 220v / 3ph / 30 Amp

110mm - 315mm (4" - 12")

42"x67"x58" 1400 lbs. 42"x67"x58" 2866 lbs.

Options

- SP 315-S operator card
- 208 to 400 power converter

Power Transformer*

SP 250-S Power Tranformer -15 KVA



Terms of useage

- Use with a dedicated line
- Must be wired by a licensed electrician
- Contact Asahi/America for further information on installation
- Must be ordered at time of tool rental
- Ideal for shop operation

* Note

Model shipped may differ from pictured unit above based on availability.

Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com **ASAHI/AMERICA** ¹³



Rental Part Number

Purchase Part Number 5869003

208v / 3ph / 30 Amp

IR/Butt


Required receptacle 208, 3 phase

9869003

Dimensions Weight **Shipping Dimensions Shipping Weight**

26"x16"x21" 275 lbs. 40"x48"x27" 300 lbs.

Comes with NEMA L15-30P





SP 110-B*

Beadless Welding Fusion Machine



Features

- Internal validation program
- Provides several QA sources
- Printer and cleanroom labels
- 110 to 230 VAC power converter
- Ideal for shop operation

Purchase Part Number5786100Rental Part Number9786100



Size Range Piping Materials Power 20mm - 63mm (1/2" - 2") Single Wall PP, PPn, PVDF 110v / 15 Amp

Dimensions Weight Shipping Dimensions Shipping Weight 26-9/16x35-3/8x25 198 lbs. 61"x39"x40" 670 lbs.

Options

- Balloons for PP or PVDF (see page 18)
- SP 110-B operator card

* Notes

Requires Balloons SP 110-B machine requires specific head to operate. Please consult chart below for sizes and part numbers

SP 110-B Beadless Heads




Size	Inches	Purchase Part Number	Rental Part Number
20mm	1/2	5786120	9786120
25mm	3/4	5786125	9786125
32mm	1	5786132	9786132
40mm	1-1/4	5786140	9786140
50mm	1-1/2	5786150	9786150
60mm	2	5786160	9786160

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

14 ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

HPF Portable Beadless

PVDF Electrofusion Welder



20mm - 63mm (1/2" - 2")

Purchase Part Number 5786000

Rental Part Number

Dimensions Weight **Shipping Dimensions Shipping Weight**

Size Range

Piping

Power

Materials

Single Wall **PVDF** 110v / 15 Amp

9786000

26"x19"x17" 100 lbs. 43"x37"x28" 365 lbs.

Options

Balloons for PVDF (see page 18)

Features

- Extremely portable
- 7 foot cable leads that are able to reach difficult areas
- Bar code entry sets parameters for each diameter
- Internal bead is eliminated using an inflatable balloon



Socket Welding PREP Tool

Part Number 58115600

Planing Tool



Features

- Quickly "PREP" pipe for socket welding
- Easy to use, impossible to misuse
- Marks insertion depth directly on pipe
- Maintenance-free operation
- Completely removes surface oxidation from PE, PP
- Reduces installation time with only one operation
- In accordance with DVS & ASTM Type B socket standards



Hand Unit		
S	ize	Part Number
mm	Inches	Part Number
20	1/2	581156005
25	3/4	581156007
32	1	581156010
40	1-1/4	581156012
50	1-1/2	581156015
60	2	581156020

Peel Remove Edge Plane


Natural oxidation occurs on polyolefin thermoplastics and must be removed in order to achieve the best bonding between pipe and socket fittings. Asahi's PREP tool effortlessly removes oxidation while planing and adds a bevel to the insertion face of the pipe. An added benefit of the onestep process is the marking of the desired insertion depth.

Complete Kit	
Item Part Number	
20-63mm Kit	581156000

Complete Kit includes:

- 20-63mm PREP tool with blades
- Manual handles (2pc)
- Driver nut
- Storage case

Item	Part Number
Handel (2 pc)	581155045
Driver Nut	581155042
Screw (2 pc)	581155001



Spare Blades (1 set + 3 pc)		
Size		Part Number
mm	Inches	Part Number
20	1/2	581155006
25	3/4	581155008
32	1	581155011
40	1-1/4	581155013
50	1-1/2	581155016
60	2	581155021

16 ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Pipe Beveller SME-1

Part Number 5686003

Beveling Tool



The SME-1 tool is ideal for beveling the ends of plastic pipes up to 63mm (2") that will be inserted into socket fusion coupling.




Rotational Scrapers PFR 110 - Part Number 5831110 PFR 225 - Part Number 5832225

Electrofusion Scraping Tool

Features

Adjustable depthSelf feeding



Asahi/America offers a wide range of scraping tools for a variety of sizes and applications. Please consult us for the best recommendation.

 Size Ranges
 PFR 110
 25mm - 110mm (3/4"- 4")

 PFR 225
 90mm - 225mm (3" - 9")



Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.



SP and HPF Balloons



SP Balloon

SP 110-B BALLOONS			
Size		PP Balloon	PVDF Balloon
mm	inch	Part Number	Part Number
20	1/2	5788405	5788305
25	3/4	5788407	5788307
32	1	5788410	5788310
40	1-1/4	5788412	5788312
50	1-1/2	5788415	5788315
63	2	5788420	5788320



HPF Balloon


HPF ELECTROFUSION BALLOONS		
Size		Part Number
mm	inch	Part Number
20	1/2	5788005
25	3/4	5788007
32	1	5788010
40	1-1/4	5788012
50	1-1/2	5788015
63	2	5788020

Socket Heater Bushings



Heater Bushings

SOCKET HEATER BUSHINGS		
s	Size	Part Number
mm	inch	Part Number
20	1/2	5797005
25	3/4	5797007
32	1	5797010
40	1-1/4	5797012
50	1-1/2	5797015
63	2	5797020
75	2-1/2	5797025
90	3	5797030
110	4	5797040





Electrofusion Couplings



PVDF Electrofusion Coupling

HPF PVDF ELECTROFUSION COUPLINGS				
Size		Part Number		
mm	inch	Part Number		
20	1/2	5479005		
25	3/4	5479007		
32	1	5479010		
40	1-1/4	5479012		
50	1-1/2	5479015		
63	2	5479020		



Proline® Electrofusion Coupling

POLYMATIC PROLINE® ELECTROFUSION COUPLINGS				
Size		Part Number		
mm	inch	Fart Number		
20	1/2	5077005		
25	3/4	5077007		
32	1	5077010		
40	1-1/4	5077012		
50	1-1/2	5077015		
63	2	5077020		
90	3	5077030		
110	4	5077040		

ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 19 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Electrofusion Couplings



Chem Proline® Electrofusion Coupling

POLYMATIC CHEM PROLINE® ELECTROFUSION COUPLINGS				
Size		Dout Number		
mm	inch	Part Number		
20	1/2	581117005		
25	3/4	581117007		
32	1	581117010		
50	1-1/2	581117015		
63	2	581117020		
90	3	581117030		
63	4	581117040		



Air-Pro® Electrofusion Coupling

POLYMATIC AIR-PRO® ELECTROFUSION COUPLINGS				
Size		Dart Norschau		
mm	inch	Part Number		
20	1/2	5817005		
25	3/4	5817007		
32	1	5817010		
40	1-1/4	5817012		
50	1-1/2	5817015		
63	2	5817020		
90	3	5817030		
110	4	5817040		
160	6	5817060		
200	8	5817080		
250	10	5817100		
315	12	5817120		

20 P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com



Single Wall Industrial Piping Systems



Supply Range Pipe and Fittings • 50 - 315mm (1/2" - 12") SDR11, 150psi



Valves

- T-21 Ball Valves: 20 63mm (1/2" 2")
- T-57 Butterfly Valves: 50 315mm (1-1/2" 12")
- T-14 Diaphragm Valves: 20 63mm (1/2" 2")
- Ball Check Valves: 20 63mm (1/2" 2")

Welding

• Butt, Socket, Electrofusion

Proline[®] (PP)

Supply Range

- Pipe and Fittings • 20 - 1200mm (1/2" - 48") SDR11, 150psi
- 110 1400mm (4" 55") SDR33, 45psi

Valves

- T-21 Ball Valves: 20 110mm (1/2" 4")
- T-57 Butterfly Valves: 50 1400mm (1-1/2" 55")
- T-14/15/G Diaphragm Valves: 20 200mm (1/2" 10")
- Ball Check Valves: 20 110mm (1/2" 4")
- Frank Series Regulating Valves: 20 110mm (1/2" 4")

Welding

• Butt, Socket, Electrofusion

Ultra Proline® (E-CTFE/Halar®)

Supply Range


- Pipe and Fittings
- 20 50mm (1/2" 1-1/2") SDR21, 150psi
- 63-110mm (2" 4") SDR21, 120psi

Valves

- T-21 Ball Valves: 20 32mm (1/2" 1")
- T-342 Diaphragm Valves: 20 63mm (1/2" 2")
- Frank Series Regulating Valves: 20 63mm (1/2" 2")

Welding

Butt



Super Proline® (PVDF)

Supply Range Pipe and Fittings

- 20 315mm (1/2" 12") SDR21, 230psi
- 90 400mm (3" 16") SDR33, 150psi

Valves

- T-21 Ball Valves: 20 110mm (1/2" 4")
- T-57 Butterfly Valves: 50 315mm (1-1/2" 12")
- T-14 Diaphragm Valves: 20 63mm (1/2" 4")
- Ball Check Valves: 20 110mm (1/2" 4")
- Frank Series Regulating Valves: 20 75mm (1/2" 2-1/2")

Welding

• Butt, Socket

Air-Pro[®] Compressed Air Piping

Supply Range

- Pipe and Fittings
- 20 110mm (1/2" 4") SDR 7.4 / 230psi
- 160 315mm (6" 12") SDR 11 / 160psi

Valves

• Ball Valves: 20 - 90mm (1/2" - 3")

Welding

· Butt, Socket, Electrofusion

ASAHI/AMERICA P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 21 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

High Purity Piping Systems

Double Wall Piping Systems

Purad[®] (Ultra High Purity PVDF)

Supply Range Pipe and Fittings

- 20 315mm (1/2" 12")
- SDR 21 / PN 16 / 230psi • 90 - 315mm (3" - 12")
- SDR 33 / PN 10 / 150psi

Valves

- T-342 Diaphragm Valves: 20 110mm (1/2" 4")
- T-343 Zero Dead Leg (ZDL) Valve: 20 110mm (1/2" 4") Over 49 different sizes and configurations
- T-21 Ball Valves: 20 110mm (1/2" 4")
- Frank Series Regulating Valves: 20 75mm (1/2" 2-1/2"

Welding

· IR/Butt, Socket, Beadless, Electrofusion

PolyPure® (Natural PP)

Supply Range

Pipe and Fittings

• 20 - 110mm (1/2" - 4") SDR 11 / PN 10 / 150psi

Valves

- T-342 Diaphragm Valves: 20 63mm (1/2" 2")
- T-343 Zero Dead Leg (ZDL) Valve: 20 63mm (1/2" 2")
- Ball Valves: 20 63mm (1/2" 2")
- 3" and 4" Valves: Only available in PP

Welding

• IR/Butt, Socket, Beadless

PP-Pure[®] (Pigmented PP)

Supply Range Pipe and Fittings

• 20 - 315mm (1/2" - 12") SDR 11 / PN 10 / 150psi

Valves

- T-342 Diaphragm Valves: 20 110mm (1/2" 4")
- T-343 Zero Dead Leg (ZDL) Valve: 20 63mm (1/2" 2")
- T-21 Ball Valves: 20 110mm (1/2" 4")

Welding

• IR/Butt, Beadless



Supply Range Pipe and Fittings • 20 - 32mm (1/2" - 1") SDR 21 / 150psi

22 P.O. Box 653 • 35 Green Street, Malden, MA 02148 • Tel: (800) 343-3618, (781) 321-5409 Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com

Duo-Pro®

Supply Range

• 1x3 through 16x20 **Materials:** Polypropylene, PVDF, & E-CTFE (Halar®)



Welding

· Simultaneous or Staggered Butt



Supply Range

• 1x3 through 12x16 Materials: Black PE100



Welding

Simultaneous or Staggered Butt

Poly-Flo[®]

Supply Range • 1x2, 2x3, or 4x6 Materials: Black Polypropylene & HDPE



Welding

Simultaneous or Staggered Butt

Pro-Lock[®]

Supply Range • 1/2x2 through 4x8 Materials: PVC & CPVC



Assembly • Simultaneous or Staggered Glue

Simultaneous or Staggered Butt

Fluid-Lok[®]

Welding

Supply Range • 1x3 through 18x24 Materials: HDPE





Welding Equipment Rental Policy

All rental equipment requires a rental agreement to be signed and completed at the time of order prior to shipping. Rental agreement is to be signed by distributor only.

Please allow 4-5 days from receipt of PO to process all rental equipment orders for shipment.

Freight: Customer pays freight from factory to the job site and job site to factory. NO exceptions. Asahi will attempt to combine machines with freight allowed pipe orders but won't guarantee this service.

Rental Rates:

•Daily Rates- Are per day, excluding weekends or National holidays.

•Weekly Rates-Are per calendar week or any part of it. We will not prorate partial weeks.

•Monthly Rates-Consist of 4 week period (28 day cycle).

•Partial months-Less than 2 weeks (14 days) will be billed per week at the monthly rate divided by 4. Greater than 2 weeks (15 + days) will carry the full monthly charge.

Asahi/America Welding Equipment Freight Insurance Policy Clarification

Due to the high value of these machines, and the sensitivity of the computers and electronics on them, damage during transportation can become very expensive. Asahi/America recommends insuring all welding equipment to the full replacement value and always accept the package from freight carriers with "possible concealed damage".

The condition of the welding equipment is the responsibility of Asahi until it leaves our facility. All rental and purchased equipment is photographed as packaged for freight pick up. Asahi is not responsible for the condition of the tool upon arrival on site. Asahi will offer customer assistance with procuring this machine insurance at time of order if requested. Customers can also choose their own carriers and insurance companies at time of order, at their cost.

All welding tools/machines are FOB Malden MA, regardless of whether they are for purchase or rental. All freight costs for all machines are the responsibility of the customer. This includes to and from the job site for rental equipment.

Asahi is always willing to work with our customers to keep costs down in today's competitive market. Tool freight costs can be minimized if tools ship with material orders that meet the standard "freight allowed" policy. (Tools ship with orders based on availability) Insurance protocols will still be in effect for automated tools even if shipped with material orders.

If you have any questions regarding this policy please contact your District Manager, or call Customer Service at our Malden, MA headquarters at 1-800-343-3618

Please consult Asahi/America's Welding Equipment Price Sheet for purchase and rental rates for all equipment and options.

Welding Equipment Catalog #WEC-13

Warrantv **TERMS AND CONDITIONS**

- Asahi/America, Inc. ("Asahi") hereby gives notice of its objection to any different or additional terms and conditions except for any such items 1. and conditions as may be expressly accepted by it in writing. The terms and conditions herein are the final expression of the parties' agreement and shall supersede any provisions, terms and conditions contained on any confirmation order or other writing buyer may give or receive and rights of the parties shall be governed exclusively by the terms and conditions hereof.
- Buyer's confirmation is accepted for merchandise selection purpose only. All orders are subject to acceptance by Asahi at its Malden, Mas-2. sachusetts office and Asahi reserves the right to reject any order in whole or in part without incurring any liability to buyer or any branch or division thereof for such order as may be rejected. Asahi shall have the right at its discretion to limit any credit to be extended hereunder or to require payment before delivery. In the event Asahi should be unable to manufacture or decide not to manufacture any product ordered, Asahi shall notify the buyer, but shall not be liable for any non-delivery of such merchandise. Buyer shall, however, accept delivery and pay for all other merchandise that is included on that order.
- 3 An order once placed with and accepted by Asahi cannot be cancelled or modified by buyer without Asahi's written consent which, if granted, will be subject to terms that will indemnify Asahi against loss.
- 4. Asahi does not accept in-store completion dates and cancellation dates will not be accepted on made-to-order product once the order has been put into production.
- Asahi orders (once accepted) may have backorders when necessary. Backorders are not subject to cancellation by buyer unless 30 days past 5. scheduled delivery date.
- 6. Delivery shall occur and risk of loss shall pass upon delivery of the merchandise sold hereunder to the carrier. Asahi will use buyer's routing guide or instructions after approval from Asahi's Traffic Department. All customers routing are F.O.B. shipping point. Asahi generates one invoice per shipment and does not include invoices with shipment.
- The buyer agrees that no shipment from Asahi will be returned from a carrier unless damage or shortages are acknowledged and signed by the 7. carrier's driver. All claims for lost or damaged shipments must be made directly by buyer to the delivering carrier at time of delivery. Shortages due to packing errors must be reported in writing within 10 days of receipt to Asahi's Customer Service Department. Adjustments can be made only if reported to Asahi in writing within that time. Buyer's requests for proof of delivery by Asahi must be made within 30 days of receipt of invoice. After 30 days, the merchandise will be considered as delivered.
- 8. Written approval from Asahi's home office must be obtained before returning defective merchandise as well as unworn, good quality merchandise of any quantity. Approval will be granted only to return unused, good quality merchandise shipped as a result of Asahi error. All returns must be sent prepaid. Upon approval by Asahi, return authorizations numbers which must be visible on the outside carton. Returns not carrying return authorization numbers will be refused delivery by Asahi and returned to send at senders expense.
- 9 Buyer agrees that it will not impose upon Asahi any handling, service or any other charges of that nature whatsoever.
- 10. Asahi will not be liable for any delay in performance of orders or contracts, or in delivery or shipment of goods, or for any damage suffered by buyer by reason of such delay in performance of orders or contracts, or in delivery or shipment of goods, or for any damage suffered by buyer by reason of such delay, when such delay is directly or indirectly caused by or in any manner arises from fire, flood, accident, riot, act of God, war, governmental interference or embargoes, strikes, labor difficulties, shortage of labor, fuel, power, materials, or supplies, transportation delays or any other cause or causes (whether or not similar in nature to any of these hereinbefore specified) beyond its control. Asahi reserves the right to discontinue product lines and make changes in products offered at any time.
- 11. Asahi products are intended to be sold in buyer's outlet(s) as addressed on this order. All branches must be separately approved. Transshipping of merchandise to approved branches of an approved account may not take place without the written approval of Asahi's Malden, MA office.
- 12. Asahi warrants only that the goods described on the face of the purchase order conform to Asahi's customary quality standards for such goods. Otherwise ASAHI MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THE ORDER. Without limiting the generality of the foregoing, ASAHI SPECIFICALLY EXCLUDES AND DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, APPLICATION OR USE AND ANY IMPLIED WARRANTY AGAINST CLAIMS BY THIRD PARTIES FOR INFRINGEMENT AND THE LIKE. This warranty constitutes the only warranty given, superseding all prior or contemporaneous oral or written representations. No Seller employee or any other person is authorized to modify this warranty or make any warranty in addition to those set forth herein.
- 13. ASAHI MAKES NO WARRANTIES, EITHER EXPRESSED, IMPLIED OR STATUTORY, INCLUDING ANY IMPLIED WAR-RANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, APPLICATION OR USE AND ANY IMPLIED WARRANTY AGAINST CLAIMS BY THIRD PARTIES FOR INFRINGEMENT AND THE LIKE FOR PRODUCTS ORDERED TO CUSTOM SPECIFICATIONS BY THE BUYER, THAT ARE EXPERIMENTAL, DEVELOPMENTAL OR PROTOTYPE PRODUCTS.
- 14. Buyer's remedies in the event of any breach by Asahi shall be exclusively limited to the return of the goods and repayment of the price. These remedies are the purchaser's exclusive remedies for breach of warranty. In no event shall buyer be entitled to claim any special, incidental, or consequential damages of any nature, including, but not limited to, loss of anticipated profits and injury to persons or property.
- 15. Payment terms shall be as set forth on the face of Asahi's invoice to buyer. Terms adjustment will be made upon request of buyer only if shipment is made more than 7 days in advance of buyer's requested ship date. Discounts will not be allowed on late payments. Discounts are applicable on merchandise only and not on freight or service charges. An interest charge of 1 1/2% percent per month (an annual rate of 18%) will be charged in states where legal on the unpaid balance owed together with cost of collection including reasonable attorney's costs. Asahi will charge a \$75.00 minimal order requirement on all orders. Any tax or duty imposed by any government will be added to the sales price.
- 16. Any waiver of any of these terms of sale by Asahi shall not be construed to be a waiver of the terms and conditions hereof as applied to subsequent transactions.
- 17. Any controversy or claim arising out of or relating to this agreement or that breach thereof shall be governed by the laws of the Commonwealth of Massachusetts. Any action or suit must be commenced within one year following delivery of the goods.

Fax: (800) 426-7058 • Website: www.asahi-america.com • Email: asahi@asahi-america.com



Another Corrosion Problem Solved.TM



35 Green St., Malden, MA 02148 Tel: 800-343-3618; 781-321-5409

Direct Sales: East (800) 232-7244 Central (800) 442-7244 West (800) 282-7244

Fax: 800-426-7058 www.asahi-america.com asahi@asahi-america.com