

# AUTOMATIC SPRINKLERS


## STANDARD SPRAY SPRINKLERS

### TY-QRF

#### Flush Pendent

- Solder type
- Light hazard/Ordinary hazard
- Features separable escutcheon with 3/8" vertical adjustment

<b>K FACTOR</b>	K=5.6 (80,6)
<b>THREAD SIZE</b>	1/2" NPT
<b>APPROVALS</b>	UL, ULC
<b>TEMPERATURE</b>	162°F/72°C
<b>ESCUTCHEON FINISH</b>	Chrome, Signal White, Jet Black
<b>SPRINKLER FINISH</b>	Chrome, Signal White, Jet Black
<b>SIN</b>	TY3261
<b>TECH DATA</b>	TFP190



Sprinkler Wrenches



### ILLUSION™

#### Concealed Standard Coverage Pendent Sprinklers

- Extra large orifice/Special hazard
- Coverage per NFPA 13
- Available with optional dust and air seal
- The ILLUSION is concealed in an enclosed escutcheon plate with flat cover for use in those applications where architecturally sensitive areas such as casinos, hotel lobbies, office buildings, churches and restaurants

<b>K FACTOR</b>	K=11.2 (161,3)
<b>THREAD SIZE</b>	3/4" NPT
<b>APPROVALS</b>	UL, C-UL
<b>TEMPERATURE</b>	160°F/71°C, - Sprinkler 139°F/59°C - Cover Plate, 212°F/100°C - Sprinkler 165°F/74°C - Cover Plate
<b>COVER PLATE FINISH</b>	Brush Chrome, Brass, Signal White, Grey White, Pure White, Custom
<b>SIN</b>	TY5521
<b>TECH DATA</b>	TFP184



Sprinkler Wrench



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.