

# SYSTEM VALVES & DEVICES

## SPECIALTY ITEMS

### FIRE DEPARTMENT CONNECTIONS

#### Straight & 90° Fire Department Connections

- Designed for fire department use to increase water pressure and volume to automatic sprinkler system or standard-pipe system
- Available in both 90° side outlet pattern and the straight through siamese pattern

**TECH DATA**

Contact Tyco for details



### AD-1


#### Automatic Drain Valve

- Designed for use with Tyco Dry Pipe, Deluge, and Preaction Valves
- Provided as a trim component for these valves, the Model AD-1 Automatic Drain Valve is used to automatically drain the normally dry alarm lines
- Maximum Pressure 250 psi (17,2 bar)

**TECH DATA**

TFP1630

- Listings and Approvals:  
UL, C-UL, FM, NYC under MEA 172-02-E



### AD-2

#### Automatic Drain Valve

- Designed to automatically drain water from fire protection equipment supply connections that are to be maintained normally dry
- Installed vertically and utilized with an open drain
- Maximum Working Pressure:  
175 psi (12,1 bar)

**TECH DATA**

TFP1632

- Listings and Approvals:  
UL & FM



### HANGERS

#### Pipe Hangers

- A full-line of pipe hangers for every fire protection need
- Manufactured to meet the quality standards that the industry demands
- Meet the requirements of NFPA 13

**TECH DATA**

Contact Tyco for details



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.