

Fast Pack - Valve/Actuator Packages

**SHIPS IN
24 HRS !**



Series 94/Type-57 Butterfly Valve

Standard Features (Sizes 1-1/2" - 4")

- UL-508 listed electric actuator
- Type-57 PVC body, PP disc, EPDM or FKM seals, wafer style
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual position indicator
- Five second cycle time*
- Mechanical brake supplied as standard for 4" Type-57 butterfly valves
- Type 4X engineered resin enclosure
- Two end of travel limit switches
- Two additional limit switches for indication
- Complete factory assembled and tested actuated valve package

**SHIPS IN
24 HRS !**



Series 94/Type-21 Ball Valve

Standard Features (Sizes 1/2" - 4")

- UL-508 listed electric actuator
- Type-21 PVC with EPDM or FKM seals, true union ball valve
- Type-21 1/2" - 2" supplied with both socket and threaded ends, 2-1/2" - 3" socket only
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual position indicator
- Five second cycle time*
- Type 4X engineered resin enclosure
- Two end of travel limit switches
- Two additional limit switches for indication
- Complete factory assembled and tested actuated valve package

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
Type-21	1/2 - 2	A94M2W	115 VAC	0.5	100%
Type-21	2-1/2 - 3	B94M2W	115 VAC	0.8	75%
Type-57	1-1/2 - 2	A94M2W	115 VAC	0.5	100%
Type-57	2-1/2 - 3	B94M2W	115 VAC	0.8	75%
Type-57	4	B94BRM2W	115 VAC	0.8	75%

*Cycle times approximate.