

AUTOMATIC SPRINKLERS

RAPID RESPONSE™ SPRINKLERS



LFII

Pendent & Recessed Pendent

- 3 mm bulb type
- Intended for use in the following scenarios:
 - wet and dry pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
 - wet and dry pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet and dry pipe sprinkler systems for the residential portions of any occupancy per NFPA 13
- Approved for special applications with beamed ceilings

K FACTOR	K=4.9 (70,6)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL, NSF
TEMPERATURE	155°F/68°C, 175°F/79°C
ESCUTCHEON	Style 20
SPRINKLER FINISH	Pure White, Signal White, Chrome Plated, Natural Brass
SIN	TY2234
TECH DATA	TFP400



Pendent & Recessed Pendent

- 3 mm bulb type
- Intended for use in the following scenarios:
 - wet pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D
 - wet pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=3.0 (43,2)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL, NSF
TEMPERATURE	155°F/68°C, 175°F/79°C
ESCUTCHEON	Style 20
SPRINKLER FINISH	Signal White, Chrome Plated, Natural Brass
SIN	TY1234
TECH DATA	TFP402



Horizontal & Recessed Horizontal Sidewall

- 3 mm bulb type
- Intended for use in the following scenarios:
 - wet pipe residential sprinkler systems for one/two-family dwellings and mobile homes per NFPA 13D,
 - wet pipe residential occupancies up to and including four stories in height per NFPA 13R
 - wet pipe sprinkler systems for the residential portions of any occupancy per NFPA 13

K FACTOR	K=4.4 (63,4)
THREAD SIZE	1/2" NPT
APPROVALS	UL, C-UL, NSF
TEMPERATURE	155°F/68°C, 175°F/79°C
ESCUTCHEON	Style 20
SPRINKLER FINISH	Signal White, Chrome Plated, Natural Brass
SIN	TY2334
TECH DATA	TFP412



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.