# AUTOMATIC SPRINKLERS SPECIAL PURPOSE SPRINKLERS

# CC1

### Combustible Concealed Space Sprinklers™, Upright

- 3 mm bulb
- Specific application sprinklers
- Provides protection of light hazard combustible, as well as non-combustible, concealed spaces requiring sprinkler protection
- Meets NFPA® Requirements for Specialty Listed Sprinklers in Combustible Concealed **Spaces**
- Allows the use of BlazeMaster® CPVC pipe in combustible concealed areas with the benefit of superior sprinkler protection for Wood truss spaces

K FACTOR	K=2.8 (40,3)
THREAD SIZE	<sup>1</sup> / <sub>2</sub> " NPT
APPROVALS	UL, C-UL
TEMPERATURE	175°F/79°C
SPRINKLER FINISH	Natural Brass
SIN	TY1189
TECH DATA	TFP630





### CC2

## Combustible Concealed Space Sprinklers™, Upright

- 3 mm bulb
- Specific application sprinklers
- Provides protection of specific light hazard combustible, as well as non-combustible, concealed spaces requiring sprinkler protection
- The CC2 Sprinklers comply with the criterion for the protection of combustible concealed spaces as described in NFPA 13.
- Allows the use of BlazeMaster® CPVC pipe in combustible concealed areas with the benefit of superior sprinkler protection for Wood truss spaces
- Can be used on steel dry pipe sprinkler systems


K FACTOR	K=4.2 (60,5) K=5.6 (80,6)
THREAD SIZE	¹⁄₂" NPT
APPROVALS	UL
TEMPERATURE	175°F/79°C
SPRINKLER FINISH	NI a ID
SIN	TY2189, TY3189
TECH DATA	TFP632














Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.