

### PCVS CONTROL VALVE SUPERVISORY SWITCH

#### Tamper & Alarm Switch

- Weather proof and tamper resistant switch for monitoring the open position of post indicator, butterfly and other types of fire sprinkler/control valves

#### TECH DATA

Contact Tyco for details



### SOLENOID VALVE

#### For Releasing Service – 1/2" (DN15)

- Used in conjunction with an electric releasing panel that is listed or approved (as appropriate) for fire protection releasing service, and where the releasing panel is operated by listed or approved (as appropriate) electric fire detectors
- Available in a variety of voltages for both normal and hazardous locations

#### TECH DATA

TFP2180



### OSY-SU

#### Tamper & Alarm Switch

- Used to monitor the open position of an OS&Y (outside screw and yoke) type gate valve
- Mounts conveniently to most OS&Y valves ranging in size from 2" (DN50) to 12" (DN300)
- Can be used on some valves as small as 1/2"
- Circulates single sprinkler flow and allows testing of flow switch without external discharge of water - replaces traditional Inspector's test procedure

#### TECH DATA

Contact Tyco for details



### 4410-RC

#### Releasing Panel

- Provides the interface between detection system, deluge or single or double interlocked preaction valve, and signaling circuit and devices in electrically actuated fire protection systems
- Separate supervisory zone provided for electronic supervision of valve position, low pressure, and other critical fire protection functions

#### TECH DATA

Contact Tyco for details

- Can be used in single zone, cross zone, sequential or cross/sequential electric deduction systems
- Has programming capability
- Listings and Approvals: UL and FM



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.