







Card Readers and Credentials Compatible with eMerge, Max 3 and MiniMax 3 Access Controllers






HID Compatible Proximity Card Readers & Credentials	
Farpointe Proximity Readers for eMerge, Max 3, and MiniMax 3	
Model/Order #	Description
P-300H 0-299100 	HID Compatible Proximity Reader, Mullion Mount HID compatible proximity reader designed to be mounted to metal door and window frames, non-contact read ranges up to 6 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, supplied with both black and off-white covers
P-500H 0-299101 	HID Compatible Proximity Reader, Single Gang Mount HID compatible proximity reader designed to be mounted to a standard single-gang J-box, non-contact read ranges up to 8 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, supplied with both black and off-white covers
P-640H 0-299102 	HID Compatible Proximity Keypad Reader HID compatible proximity reader and keypad designed to be mounted to a standard single-gang J-box, non-mechanical capacitive keypad, non-contact read ranges up to 6 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, supplied with both black and off-white covers
Farpointe Proximity Credentials for eMerge, Max 3, and MiniMax 3	
PSC-1H 0-299106 	HID Compatible Proximity Clamshell Card HID compatible, standard light proximity card, provides maximum read range in a durable clamshell-style package, beveled edges, constructed of durable ABS plastic, vertical slot punch, off-white, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
PSM-2PH 0-299107 	HID Compatible Proximity ISO PVC Card HID compatible, multi-technology proximity card, ISO thickness glossy PVC card can be printed on front and back, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
PSK-3H 0-299108 	HID Compatible Proximity Keyfob HID compatible, proximity keyfob, constructed of durable ABS plastic, brass eyelet, small size, light-gray, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)




USA & Canada (800) 421-1587 & (800) 392-0123
 (760) 438-7000 - Toll Free FAX (800) 468-1340
www.linearcorp.com

Smart Card Readers & Credentials

Farpointe Smart Card Readers for eMerge, Max 3, and MiniMax 3

Model/Order #		Description
Delta 3H 0-299103		Smart and Proximity Card Reader, Mullion Mount 13.56 Mhz smartcard and 125 kHz HID compatible proximity reader designed to be mounted to metal door and window frames, non-contact read ranges up to 3 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, black cover
Delta 5H 0-299104		Smart and Proximity Card Reader, Single Gang Mount 13.56 Mhz smartcard and 125 kHz HID compatible proximity reader designed to be mounted to a standard single-gang J-box, non-contact read ranges up to 3.5 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, black cover
Delta 6.4H 0-299105		Smart and Proximity Card Keypad Reader 13.56 Mhz smartcard and 125 kHz HID compatible proximity reader and keypad designed to be mounted to a standard single-gang J-box, non-mechanical capacitive keypad, non-contact read ranges up to 3 inches, horizontal and vertical mounting slots, electronics secured in tamper-resistant epoxy potting, black cover

Farpointe Smart Credentials for eMerge, Max 3, and MiniMax 3

DC1-1 0-299109		Clamshell Contactless Smart Card, 1K byte Smartcard 13.56 MHz ISO 14443 Type A card, 1K storage, provides maximum read range in a durable clamshell-style package, beveled edges, constructed of durable ABS plastic, vertical slot punch, off-white, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DC4-1 0-299110		Clamshell Contactless Smart Card, 4K byte Smartcard 13.56 MHz ISO 14443 Type A card, 4K storage, provides maximum read range in a durable clamshell-style package, beveled edges, constructed of durable ABS plastic, vertical slot punch, off-white, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DM1-3 0-299111		Printable Contactless Smart Card, 1K byte Smartcard 13.56 MHz ISO 14443 Type A card, 1K storage, ISO thickness glossy PVC card can be printed on front and back, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DM4-3 0-299112		Printable Contactless Smart Card, 4K byte Smartcard 13.56 MHz ISO 14443 Type A card, 4K storage, ISO thickness glossy PVC card can be printed on front and back, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DM1-3S 0-299113		Printable Contactless Smart Card with Mag Stripe, 1K byte Smartcard 13.56 MHz ISO 14443 Type A card with mag stripe, 1K storage, ISO thickness glossy PVC card can be printed on front and back, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DM4-3S 0-299114		Printable Contactless Smart Card with Mag Stripe, 4K byte Smartcard 13.56 MHz ISO 14443 Type A card with mag stripe, 4K storage, ISO thickness glossy PVC card can be printed on front and back, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DK1-3 0-299115		Contactless Smart Card Keyfob, 1K byte Smartcard 13.56 MHz ISO 14443 Type A keyfob, 1K storage, constructed of durable ABS plastic, brass eyelet, small size, light-gray, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)
DK4-3 0-299116		Contactless Smart Card Keyfob, 4K byte Smartcard 13.56 MHz ISO 14443 Type A keyfob, 4K storage, constructed of durable ABS plastic, brass eyelet, small size, light-gray, Wiegand 26-bit format, Facility Code 11, (price per lot, sold in lots of 25 only)



USA & Canada (800) 421-1587 & (800) 392-0123
 (760) 438-7000 - Toll Free FAX (800) 468-1340
www.linearcorp.com