

IDENTIFICATION

BIOSCRIPT 4G V-FLEX LITE™

SLIM AND SLEEK IDENTIFICATION TERMINAL

FOR PHYSICAL ACCESS CONTROL



Large user storage capacity (5,000 in 1:N / 25,000 in 1:1)

Optional integrated card readers (Prox®, iCLASS®, MIFARE®, DESFire®)

IP 65 rated: indoor and outdoor capabilities

BIOSCRIPT 4G V-FLEX LITE™

SLIM AND SLEEK IDENTIFICATION TERMINAL

FOR PHYSICAL ACCESS CONTROL

The 4G V-Flex Lite™ is ideal for deployments both large and small. The device is the smallest biometric form-factor in the 4G product lineup, making it ideal for mullion or single gang mounting requirements.



TECHNICAL SPECIFICATIONS

- **Network/Communication Options:**
Ethernet (TCP/IP) and RS485
PC Connection: USB
- **Input/Outputs:**
Option for Wiegand in/out (customizable format up to 512 bits), 2 General Purpose Inputs (REX, Door Contact), 1 Form C Relay Output, 1 General Purpose Output
- **Integrated Door Relay Details:**
30V DC @1A Deadbolt, electromagnetic (EM) lock, door strike, automatic door
- **Authentication Options:**
Finger only, Card + Finger
- **Internal Card Reader Options:**
Prox® or iClass®/MIFARE®/DESFire® Card Reader
- **Audio:**
Supports .wav custom files
- **Template Storage Capacity:**
- 25,000 in 1:1 authentication mode
- 5,000 in 1:N identification mode
- **Transaction Log Capacity:**
100,000 transaction logs stored on device
- **Power Supply:**
12 to 24V DC
Current Draw: 500mA @12 VDC
- **Dimensions (H*W*D):**
172*52*51 mm
6.7*2.05*2.00 inches
- **Operating Temperature:**
-20°C to 65°C; -5°F to 150°F
- **Regulatory Approvals and Certifications:**
CE, FCC, RoHS, IC RSS210, IP 65
- **Administration Software Options:**
SecureAdmin Lite™ Software or SecureSDK™

Morpho

Phone: +33 (0)1 58 11 73 42 - Fax: 33 (0)1 58 11 25 50 - www.morpho.com - www.biometric-terminals.com
Registered Office: 11, boulevard Gallieni - 92130 Issy-les-Moulineaux - FRANCE
Société anonyme au capital de 159.876.075 euros - 440 305 282 RCS Nanterre