

Linear | Interlogix® Compatible Wireless Sensors

ITIFOB01

Wireless Key FOB



- Belt/Wall Clip Option
- Resist Accidental Button Press
- Tactile Button Feel

ITIMDW01

Door/Window Wireless Sensor



- Vanishing Design
- 5 Yr Lithium Battery
- 7/8" Activation Gap

ITIRDW01

Recessed Door Sensor



- Compact Design
- Rare Earth Magnet
- 1.25" Activation Gap

ITIPIR01

Pet Immune Wireless PIR



- Selectable 33/55Lb Pet Immunity
- 30' x 50' Detection Area
- Corner/Wall Mount Bracket

ITIGLB01

Glass Break Wireless Sensor



- 2 Stage Detector Circuit
- 12ft/360 Degree Coverage
- Built-in Glass Break and RF Test

ITIDWA01

Door/Window Wireless Sensor



- Slim Design
- Aux Input
- 7/8" Activation Gap

Compatibility

Works with all Wireless Interlogix Alarm Panels

- Simon
- NX Series
- Concord Series

More Detailed Specs on Reverse Side

Compatible with all **Interlogix** Receivers

Linear | Interlogix Compatible Wireless Sensors



ITIFOB01 Wireless Key FOB

Battery Life: 3 years
Battery: (2) CR2025 Lithium
TX Range: Up to 300 feet
Size: 2.5 x 1.2 x 0.375 in (H x W x D)
Accessories: Visor Clip, Belt clip
Order No: **ITIFOB01**



ITIGLB01 Glass Break Wireless Sensor

Battery Life: 3 years
Battery: 2 x CR123A
Detection Range: 12ft
TX Range: Up to 500 feet
Size: 4.625 x 1.875 in (D x H)
Accessories: Screws
Order No: **ITIGLB01**



ITIMDW01 Door/Window Wireless Sensor

Battery Life: 5 years
Battery: CR2032
Range: Up to 500 feet
Size: 1.5 x 1.0 x .375 (H x W x D)
7/8" Wide Gap
Accessories: Double Sided Tape, Screws
Order No: **ITIMDW01**



ITIPIR01 Pet Immune Wireless PIR

Battery Life: 5 years
Battery: CR123A
33Lb or 55Lb Pet Immune Detection
Detection Area: 30 ft x 50 ft
TX Range: Up to 500 feet
Size: 3.5 x 2.3 x 1.9 in (H x W x D)
Accessories: Screws, Corner and Wall Mount Brackets
Order No: **ITIPIR01**



ITIRDW01 Recessed Door Sensor

Battery Life: 5 years
Battery: CR2
Range: Up to 500 feet
Size: 0.75 x 2.5 in (D x H)
1.25" Wide Gap
Accessories: Mounting Screws,
Screw Secured Cover
Order No: **ITIRDW01**



ITIDWA01 Door / Window Wireless Sensor

Battery Life: 5 years
Battery: 2 x CR2032
TX Range: Up to 500 feet
Accessories: Screws
Order No: **ITIDWA01**

Common Specifications

Frequency: 319.5Mhz
Operating Temperature: -5° to 55° C
Operating Relative Humidity: 5 to 90%, non-condensing

Compatible with all **Interlogix** Receivers

Interlogix is a trademark of Interlogix, Inc., a United Technologies Corporation.

Linear[®]
Building On Innovation.