

D8TURBO

HD 1080p Turbo HD Outdoor Dome Camera



epcom
POWERED BY HIKVISION

► Camera

Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	2.8 - 12mm @ F1.4 Angle of view: 92° - 32°
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 80°, Rotation: ± 90°
Day & Night	ICR
Wide dynamic range	120 dB
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S/N Ratio	More than 52dB

► General

Working Temperature/ Humidity	-20°C-60°C(-4°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12 VDC: Max. 4.5W ; 24 VAC: Max. 6.5W
IR Range	Up to 40m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89")
Weight	880 g (1.95 lb)

► Menu

Scene	Indoor, outdoor, indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, japanese, CHN1, CHN2, korean, german, french, italian, spanish, polish, russian, portuguese, dutch, turkish, hebrew and arabic
Function	Eclipse, digital noise reduction, digital zoom (62X), slow shutter, mirror, defog, defect pixel correction, SMART-DZOOM

► Key Features

HD1080p video output
Adopt HDTVl Technology
2.8 - 12mm vari-focal lens
OSD menu, 3D DNR, Smart IR
Up to 40m IR distance
IP66 weatherproof
Up the Coax(via coaxial cable)
120 dB Wide Dynamic Range