

IDENTIFICATION

BIOSCRIPT 4G V-STATION WR™

UNMATCHED PERFORMANCE IN A WEATHER RESISTANT DESIGN



IP 65 rated for outdoor environments

Built in hood and specialized components for Weather Resistant protection

Temperature range between -20°C and 60°C (-5°F to 140°F)

Largest verification capacity in the industry (500,000 users in 1:1)

Optional integrated card readers (Prox®, iClass® or MIFARE®/DESFire®)

Full IP and PoE Enabled (Optional Wireless LAN)

BIOSCRIPT 4G V-STATION WR™

UNMATCHED PERFORMANCE IN A WEATHER RESISTANT DESIGN

When you need a versatile device for use in moderate outdoor conditions and cannot compromise on offering superior performance and usability, the 4G V-Station WR™ is the right solution for you.

The Weather Resistant (WR) models have specialized components and a built in hood that offer protection against certain outdoor elements.

TECHNICAL SPECIFICATIONS



- **Network/Communication Options:** LAN, WAN, RS485 and optional Wireless LAN
PC Connection: USB, RS232
- **External Media:** USB memory
- **Input/Outputs:** Wiegand (Customizable format up to 512bits),
3 General Purpose Inputs,
3 General Purpose Outputs (extendable to 6 outputs)
- **Internal Card Reader options:** Prox®, iClass®, MIFARE®/DESFire®
- **Duress finger option**
- **Transaction Log Capacity:** 1 million transaction logs stored on device
- **Sensor:** 500 dpi optical
- **Display:** 2.5" QVGA Color LCD
- **Speaker:** Full Audio Support
- **Keypad:** 3x4 Backlit Keypad (Blue), Programmable Function Keys for 16 Time & Attendance events, Multi Directional Navigation Keys
- **Power Supply:**
 - 12 to 24V DC
 - Current Draw: 500mA @12V DC
 - Power Over Ethernet (PoE)
 - Power Indicator: LED indicator (Blue)
- **Integrated Door Relay:** Deadbolt, electromagnetic (EM) lock, door strike, automatic door
- **Tamper Detection**
- **Mounting:** Flush mount with quick-tilt top design for easy maintenance
- **Dimensions (H*W*D):** 191*174*57 mm
7.52*6.82*2.25 inches
- **Outdoor Ideal Deployment:** Areas that offer degree of protection from direct elements
- **Operating Temperature:** -20°C to 60°C
-5°F to 140°F
- **Regulatory Approvals and Certifications:** CE, FCC, RoHS, IC RSS210, IP 65
- **Administration Software Options:** SecureAdmin™ Software or Secure SDK™

	4G V-Station WR™ Base	4G V-Station WR™ Prox®	4G V-Station WR™ iClass®	4G V-Station WR™ MIFARE®/DESFire®
Template Storage Capacity	500,000 in 1:1 verification mode 10,000 in 1:N identification mode 50,000 in 1:N identification mode with binning (option)			
Authentication Modes	<ul style="list-style-type: none"> • Finger only • Finger + PIN • PIN only 	<ul style="list-style-type: none"> • Prox Card + Finger • Prox Card only • Finger only • Finger + PIN • PIN only • Prox Card + PIN + Finger 	<ul style="list-style-type: none"> • Finger only • Card only • Smart Card + Finger • Smart Card + Finger + PIN 	<ul style="list-style-type: none"> • Finger only • Card only • Smart Card + Finger • Smart Card + Finger + PIN