



26-INCH PVM (PUBLIC VIEW MONITOR)

- On-board CCTV Camera
- Color Hi-Resolution or Wide Dynamic Range Camera Options
- Varifocal Lens with Auto-Iris
- 1366 x 768 Resolution
- Bright 450 cd/m2 Display
- HDMI, VGA Inputs
- 3D Comb Filter with De-Interlace
- 2x BNC Inputs, 1x BNC Loop Out
- VESA Compliant Hole Pattern
- Energy Saving Light Sensor.

S P E C I F I C A T I O N S

Monitor Specifications		
Product Description	PVM Line 26" Color Cam	PVM Line 26" WDR Cam
Product ID	PVM-26CH211-B	PVM-26WD211-B
On-Board Camera Type	Color Hi-Res	Wide Dynamic Range
Lens Type	Varifocal Lens	
Screen Size	26"	
Aspect Ratio	16:9	
Resolution	1366 x 768	
Brightness (cd/m2)	450	
Response Time	8ms (G-to-G)	
Viewing Angle (H/V)	178° / 178°	
Contrast Ratio	4000:1	
Pixel Pitch	0.4215 x 0.4215mm	
Digital Inputs	HDMI, VGA	
Composite Inputs / Outputs (BNC)	1 / 2	
Power Consumption	< 130W	
Features - Signal Filter	3D-Comb, De-Interlace	
Features - PIP - 1 composite, 1 digital	Yes	
Features - PIP - 2 composite or digital	Yes	
Wall Mount Hole Pattern	100 x 100mm, 200 x 100mm	
Remote	Included	
Light Sensor	Yes	
Power Supply	Included adapter: 24VDC, 5.42A	
Aux. 12VDC Power Output	Yes	
Connector Location / Secured	Bottom / Yes	
Approvals	UL, FCC, RoHS	

Camera Specifications		
Camera Type	Color Hi-Res	Wide Dynamic
Image Sensor	1/3" Sony Super HAD CCD	1/3" Pixim DPS Sensor
Signal System	NTSC	
Effective Pixels	768 (H) x 494 (V)	720 (H) x 480 (V)
Resolution	540TVL	540TVL
Mimumum Illumin	0.1Lux/F1.2	0.5Lux/F1.2;0.08
Dynamic Range	n/a	101dB Typ., 120dB Max
S/N Ratio	>48dB	>50dB
Control Method	n/a	OSD
Electronic Shutter	1/60 - 1/100,000 sec	Auto
White Balance	Auto	ATW/AWB/Manual/ATW Extend
AGC	Auto	
BLC	Auto	
Gamma Correction	0.45	
Varifocal Lens	2.8-11mm, AI, IR	
Power Consumption	93 mA	150mA
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F), 90% RH Max	



1950 Camino Vida Roble, Suite 150
 Carlsbad, CA 92008
 Tel: 760.438.7000 800.421.1587
 www.aigismech.com • www.linearcorp.com