

Specifications

*Advanced Steam Boiler Technology
that is Safe, Efficient and Reliable*

CLAYTON FLUID HEATERS OFFER:

- **COMPACT SIZE**

Clayton steam generators will normally fit in any available area while also reducing construction costs on new building installations.

- **FUEL EFFICIENT**

High efficiency which is inherent with the Clayton design translates into lower operating costs and improved overall system operation

- **RESPONSIVE**

Very rapid response to changing steam loads. Clayton steam generator will automatically modulate to match your steam load profile while maintaining system steam pressure

- **SAFE**

Our once through design eliminates the possibility of a steam or water side explosion. The Clayton steam generator is simply the safest steam boiler on the market.

- **LESS WATER WASTE**

Clayton's design concentrates TDS blow down significantly which reduces wasted fuel, water and chemical costs.

- **FAST START**

Full steam pressure and output in minutes from a cold start-up saves fuel and labor cost over conventional designs. Eliminates wasted fuel from idling.

- **AUTOMATIC**

Operation is automatically controlled and the Clayton steam generator can be started from a single switch or remotely using an automatic start option.

- **LOW WEIGHT**

The relatively light weight means that all sizes of Clayton steam generators can be easily moved and installed even in areas with limited structural support.

- **RELIABLE**

Reliability of the Clayton steam generator is field proven and unsurpassed. This results in greatly reduced maintenance and attendance.

- **HIGH QUALITY STEAM**

Steam Quality in excess of 99.5% dry is assured at all times. This is the highest steam quality of any competitive design. Less water and impurities further increase your energy efficiency.

MODEL E804-DZ FLUID HEATER 800 BHP



Clayton
INNOVATIVE STEAM SOLUTIONS

S
A
V
E
S

F
U
E
L

*

S
A
V
E
S

S
P
A
C
E

*

S
A
V
E
S

T
I
M
E

*

S
A
V
E
S

M
O
N
E
Y

SPECIFICATIONS

MODEL E804

	MODEL E804 Standard	MODEL SE804 with Super Economizer	MODEL EG804-FMB with Low NOx Burner	MODEL SEG804-FMB with Low NOx Burner and Super Economizer
BOILER HORSEPOWER	800	800	800	800
HEAT INPUT, BTU/hr	Oil 32,265,060 Gas 32,658,537	31,139,535 31,505,882	NA 33,061,728	NA 31,505,882
NET HEAT OUTPUT, BTU/hr	26,780,000	26,780,000	26,780,000	26,780,000
EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam)	27,600 lbs/hr	27,600 lbs/hr	27,600 lbs/hr	27,600 lbs/hr
DESIGN PRESSURE (see note 1)	65 - 500 psig	65 - 500 psig	65 - 500 psig	65 - 500 psig
STEAM OPERATING PRESSURE (determined by design pressure)	60 - 450 psig	60 - 450 psig	60 - 450 psig	60 - 450 psig
OIL CONSUMPTION at maximum steam output (see note 2)	229 gph	221 gph	NA	NA
GAS CONSUMPTION at maximum steam output (see note 3)	32,659 cfh	31,506 cfh	33,062 cfh	31,506 cfh
BURNER CONTROLS modulating	5 to 1 Turndown	5 to 1 Turndown	4 to 1 Turndown	4 to 1 Turndown
EFFICIENCY				
oil-fired efficiency %	83%	86%	NA	NA
gas-fired efficiency %	82%	85%	81%	85%
ELECTRIC MOTORS, HP (see note 4)	Blower Pump	Blower Pump	Blower Pump Cooling	Blower Pump Cooling
design pressure 15-300 psig	75 50	75 50	100 50 7.5	100 50 7.5
design pressure 301-500 psig	75 60	75 60	100 60 7.5	100 60 7.5
ELECTRIC FLA, based on 460 V (see note 5)				
design pressure 15-300 psig	194	194	239	239
design pressure 301-500 psig	207	207	252	252
GAS SUPPLY PRESSURE REQUIRED	5 to 10 psig	5 to 10 psig	5 to 10 psig	5 to 10 psig
ATOMIZING AIR REQUIRED (see note 6)				
Capacity	30 scfm	30 scfm	N/A	N/A
Minimum pressure	70 psig	70 psig	N/A	N/A
AIR SUPPLY REQUIRED (FMB -see note 7)	N/A	N/A	5 scfm @ 3 to 150 psig	5 scfm @ 3 to 150 psig
WATER SUPPLY REQUIRED	4,240 gph	4,240 gph	4,240 gph	4,240 gph
HEATING SURFACE	1,523 sq.ft.	1,701 sq.ft.	1,523 sq.ft.	1,701 sq.ft.
EXHAUST STACK DIAMETER, o.d.	35.75 in.	35.75 in.	35.75 in.	35.75 in.
APPROXIMATE OVERALL DIMENSIONS				
length	151 in.	151 in.	160 in.	160 in.
width	133 in.	133 in.	149 in.	149 in.
height	198 in.	224 in.	198 in.	224 in.
WEIGHT				
installed - wet	28,535 lbs	32,244 lbs	28,835 lbs	32,544 lbs
shipping	24,500 lbs	27,800 lbs	24,800 lbs	28,100 lbs
FW pump skid	3,200 lbs	3,200 lbs	3,200 lbs	3,200 lbs

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) Oil fired units also use a separate motor driven fuel oil pump - 3/4 HP

5) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2.

6) Atomizing air required for oil burner.

7) Compressed air required for FMB.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

**Europe, Africa &
Middle East Headquarters**
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service