


COMMERCIAL PRODUCTS CATALOG

Common Ball Valve Options

Apollo offers these options on the 70 Series as well as many other valve series. Note: Not all options are available on all sizes and models. Review the latest submittal sheet or contact the factory to determine availability.

Suffix No.

-27



LATCH LOCK

Sliding lock mechanism secures handle in open or closed position. Valve can also be padlocked open or closed.

-30



CAM-LOCK® HANDLE

Patented Cam-Lock® handle gives valve extra protection against accidental operation. Reliable quarter-turn shut-off from a versatile, ruggedly built valve.

- RPTFE seats and stuffing box ring
- Rated 600 psig CWP, non-shock
- Available for the following Series: 70, 71, 73A, 76, 82, 83, 86, 87, 89, 9A, 92, and 96

-32 and -83



STAINLESS STEEL TEE HANDLE AND NUT

Increased corrosion resistance versus the plated steel -07 option.

- -32 for standard bronze
- -83 for 77B/77BLF and 77C/77CLF Series

-41



BALL VALVE WITH AUTOMATIC DRAIN

When this valve is closed for maintenance of pneumatic tool, downstream pressure from valve to tool is automatically drained to atmosphere to prevent accidental operation of the tool, causing possible injury.

- Conforms to certain OSHA requirements in pneumatic installations
- Easy, safe maintenance of pneumatic tools
- Cannot be used where drained media could cause damage
- Temperature range: 50°F to 200°F
- Rated 125 psig CWP, non-shock air or water
- Includes directional arrow for correct installation
- Available with latch lock option, specify -27 -41 suffix
- Available for the following Series: 70, 71, 75, and 78

-48



STAINLESS STEEL OVAL HANDLE

- Available for the following Series: 70, 71, 73A, 76, 76F, 77, 82, 83, 85, 86, 89, 9A, 92, and 96

-94



BALL VALVE WITH BALANCING STOP AND STEM EXTENSION

Ideal for HVAC systems. Stop plate and a 2-1/4" stem extension combination to accommodate insulation and handle repositioning. *Contact customer service for exact handle dimensions*