



JPEG2000 HD Panoramic Dome Camera

JPEG2000 HD panoramic dome cameras feature four 2 MP sensors for a total resolution of 8 MP. A single installation provides high-resolution 180° or 360° coverage with lenses that are all pre-focused for no-fuss installation. This camera is ideal for monitoring indoor and outdoor environments for sectors such as education, banking, retail, accommodation, and hospitality or for any location where installation points are limited.

KEY FEATURES

Panoramic Wide-Area Coverage

Easy Installation

Multi-Megapixel

Alarm Input and Outputs

Audio Recording

BENEFITS

Four 2 MP sensors provide 180° or 360° coverage in high-definition from a single camera, minimizing installation needs.

Factory installed pre-focused lenses means no lens adjustment required during installation.

Live and post-incident digital PTZ.
Reduce number of camera installations.

Synchronize with external alarms and integrate motion detection into your current alarm system.

Record high-quality audio from any line input or microphone source.

Resolution	Pixel Layout	Sensor Format	Lens	Maximum Images Per Second (IPS)	Camera Type	Sensitivity (lux)	Model	Recommended Application
8 MP	1600 x 1200 per sensor	4 x 1/4"	4 x 4.4mm f/2.0	7 (28 for all sensors)	180° Panoramic Color Dome	0.6 in Color	8 MP-HD-DOME-180	Complete high-definition coverage of a 180°-wide field of vision from a single camera without any distortion
8 MP	1600 x 1200 per sensor	4 x 1/4"	4 x 2.4mm f/2.0	7 (28 for all sensors)	360° Panoramic Color Dome	0.6 in Color	8 MP-HD-DOME-360	Complete 360° high-definition coverage of a room from a central mounting point using a single camera

JPEG2000 HD PANORAMIC DOME CAMERA OPTIONS

Model No.	Descriptions
H	Factory-installed heater unit

JPEG2000 HD PANORAMIC DOME CAMERA ACCESSORIES

Model No.	Descriptions
DOME-INDE-PLT	Indoor electrical-box mounting plate; allows surface mounting with side cable access and mounting to an electrical box
DOME-OD-BASE	Outdoor mounting base; creates an IP66 enclosure with IK10 impact rating for outdoor environments
DOME-OD-PEND	Outdoor pendant mount; creates an IP66 enclosure with IK10 impact rating for connection to industry-standard pendant mounts
PEND-GS-WALL	Gooseneck wall bracket for use with DOME-OD-PEND
DOME-IND-CEL	In-ceiling mount; allows the camera to be ceiling mounted with only the external dome cover showing
IND-CEL-PNL	Metal ceiling panel for use with the DOME-IND-CEL to replace or reinforce the existing ceiling tile in suspended ceiling installations
DOME-SMOKE	Replacement smoked transparent cover

