



H.264 HD Dome Camera

H.264 HD dome cameras (available in 1 MP to 2 MP resolutions) are great for monitoring both daytime and nighttime activities and are available in four configurations: indoor, in-ceiling, outdoor, and outdoor pendant. They feature an integrated lens for remote focus and zoom control and are ONVIF compliant for no-hassle integration. The H.264 HD dome camera is effective for monitoring a variety of environments, particularly those requiring vandal resistance, such as banks, schools, retail outlets, municipal grounds and buildings, hotels, bars and restaurants.

KEY FEATURES

Remote Zoom and Focus

Flexible Installation

Industry Standards

H.264 and MJPEG Compression

Ready for the Environment

BENEFITS

With remote zoom and focus included in the lens, installation only requires mounting and aiming.
Auto-detection and auto-configuration of cameras.

Versatile three-axis adjustment for simple mounting in any configuration provides flexible and efficient installation. Available for indoor, in-ceiling, outdoor, and outdoor pendant.

ONVIF compliance allows for support from leading video management systems, including Avigilon Control Center.

H.264 compression provides high image quality with low bandwidth and minimal storage requirements for high frame rates.

Multiple independent streams allow optimization of storage and bandwidth.

IP66 weather rating.
IK10 impact rating for vandal resistance.

Resolution	Pixel Layout	Sensor Format	Lens	Maximum Images Per Second (IPS)	Sensitivity (lux)	Models	Camera Type
1 MP	1280 x 720	1/3"	3-9mm, f/1.2 remote zoom & focus	30	0.2 in Color 0.02 in Monochrome	1 MP-HD-H264-D1	Indoor
						1 MP-HD-H264-DO1	Outdoor, IP66 rated, IK10 and vandal-proof, integrated heater
						1 MP-HD-H264-DP1	Outdoor, IP66 rated, IK10 and vandal-proof, pendant mounted, integrated heater
						1 MP-HD-H264-DC1	In-ceiling
2 MP	1920 x 1080	1/3"	3-9mm, f/1.2 remote zoom & focus	30	0.2 in Color 0.02 in Monochrome	2 MP-HD-H264-D1	Indoor
						2 MP-HD-H264-DO1	Outdoor, IP66 rated, IK10 and vandal-proof, integrated heater
						2 MP-HD-H264-DP1	Outdoor, IP66 rated, IK10 and vandal-proof, pendant mounted, integrated heater
						2 MP-HD-H264-DC1	In-ceiling

