

- Mechanical Force Gauges
- Digital Force Gauges
- Torque Testers
- Manual Test Stands
- Motorized Test Stands
- Attachments
- Push / Pull Testers
- Crimp Testers
- Peel Testers
- Spring Testers
- Puncture Testers
- Compression Testers
- Strength Testers
- Force Data Acquisition
- Torque Data Acquisition
- Calibration/Repair
- Trade In

Home | digital force gauges

Digital Push/Pull Force Gauges with Output – Series DS2



- Simple operation, easy-to-use, accurate
- Large easy-to-read LCD display
- Ergonomic, durable, heavy-duty metal construction
- Push-button selectable lbf, kgf, and Newton units
- RS-232C, Digimatic and analog outputs
- Programmable High/Low setpoints with LCD indicators
- Overload capacity 200% F.S.
- Overload alarm, display flashes at overload limit
- Low battery icon
- Runs on internal NI-MH batteries or AC adapter
- Selectable real time or peak mode operation
- Push-button tare function n Reversible display
- Set of six adapters, AC charger/adaptor and carrying case

PRICING
DELIVERY
SUPPORT



}
[Dimensions](#) | [Data Acquisition](#)
}

DS2 digital force gauges feature a large, easy-to-read LCD display and simple push-button operation. An ergonomic metal housing protects the highly accurate loadcell and electronics in tough industrial environments.

When measuring, units of measure and a tension or compression icon are displayed. A battery icon indicates the NI-MH batteries are low. If an overload occurs the display will flash to warn you.

If desired, you can program high/low setpoints to enable Go/NoGo testing using the LCD indicators. Standard outputs (RS-232C, Digimatic, and ± 1 VDC analog) enable you to acquire data for permanent record.

Choose a range or ranges that best suit your application. All DS2 gauges are sold in a complete kit with gauge, hard plastic carrying case, a set of six measuring adapters and AC adapter/charger. All DS2 gauges can run on the internal NI-MH batteries or the AC adapter/charger. An optional handle to facilitate the measurement of heavy loads is also available.



SW-1 Data Acquisition Software (optional)

You can acquire and analyze real-time data from any Imada gauge with an RS-232 port directly into any Windows program. Log and chart measurements as well as statistical information and control the gauge from your computer.

DB-1 Data Input Button (optional)

DB-1 is a simple, compact, one channel interface that enables the user to send measurement data to a PC running SW-1, Imada data acquisition software or other software. The data input button simplifies peak measuring tests because it 'zeros' the gauge after sending the data to the computer eliminating the need to reset manually for each test.

DS2 Specifications	
Accuracy	$\pm 0.2\%$ F.S., ± 1 LSD
Selectable Units	lbf(ozf), kgf(gf) or Newtons
Overload Capacity	200% of F.S. (Overload indicator flashes beyond 110% of



DS2 Kit

	F.S.)
Data processing speed	1,000 data/second (30 data/second rate selectable)
Display Update	10 times/second
Power	Rechargeable Ni-MH battery pack or AC adapter
Battery Indicator	Display flashes battery icon when battery is low
CPU	8-bit CMOS
Setpoints	Programmable high/low setpoints with LCD indicators
Outputs	RS-232C, Digimatic and ± 1 VDC analog output
Operating Temp.	32° to 100°F (0° to 40°C)

DS2 Ranges (Resolution) Accuracy: $\pm 0.2\%$ F.S. ± 1 LSD			
Model	Capacity (Resolution)		
	Pounds/Ounces	Kilograms/Grams	Newtons
DS2-0.4	7.00 (0.01 ozf)	200.0 (0.1 gf)	2.000 (0.001 N)
DS2-1	18.00 (0.01 ozf)	500.0 (0.1 gf)	5.000 (0.001 N)
DS2-4	4.400 (0.001 lbf)	2.000 (0.001 kgf)	20.00 (0.01 N)
DS2-11	11.00 (0.01 lbf)	5.000 (0.001 kgf)	50.00 (0.01 N)
DS2-44	44.00 (0.01 lbf)	20.00 (0.01 kgf)	200.0 (0.1 N)
DS2-110	110.0 (0.1 lbf)	50.00 (0.01 kgf)	500.0 (0.1 N)
DS2-220	220.0 (0.1 lbf)	100.0 (0.1 kgf)	1000 (1 N)

For capacities over 220 lbf use [ZPH Series](#)