



**Viega ProPress adapter  
Zero Lead**  
 - For use with ASTM B88 tubing  
 - Bronze  
 - Street, female pipe thread  
**Model 2912.1ZL**

FTG	FPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.071	5	<b>79425</b>	8
1/2	1/2	0.108	5	<b>79430</b>	8
1/2	3/4	0.141	5	<b>79435</b>	8
3/4	1/2	0.113	5	<b>79440</b>	8
3/4	3/4	0.145	5	<b>79445</b>	8
1	1/2	0.179	1	<b>79455</b>	8
1	1	0.274	1	<b>79450</b>	8
1 1/4	1/2	0.278	1	<b>79460</b>	8
1 1/4	1 1/4	0.402	1	<b>79465</b>	8
1 1/2	1 1/2	0.517	1	<b>79470</b>	8
2	2	0.844	1	<b>79475</b>	8



**Viega ProPress XL adapter  
Smart Connect feature**  
 - For use with ASTM B88 tubing  
 - Copper  
 - Press connection, female pipe thread  
Components  
 EPDM sealing element  
Note  
 Must be installed with Viega ProPress XL-C rings and V2 actuator.  
**Model 0912XL**

P	FPT	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	1.821	1	<b>20819</b>	8
3	3	2.931	1	<b>20829</b>	8
4	4	4.404	1	<b>20839</b>	8



**Viega PEX Press adapter  
Smart Connect feature, Zero Lead**  
 - For transitioning between Viega PEX Press and Viega ProPress  
 - Bronze  
 - Press connection  
Components  
 EPDM sealing elements  
Note  
 ProPress tool and jaw required  
**Model 2813PZL**

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.075	10	<b>99620</b>	6
1/2	3/4	0.114	10	<b>99626</b>	6
3/4	1/2	0.077	10	<b>99630</b>	6
3/4	3/4	0.113	10	<b>99640</b>	6
1	3/4	0.136	10	<b>99645</b>	6
1	1	0.185	10	<b>99660</b>	6
1 1/4	1	0.231	5	<b>99665</b>	6
1 1/4	1 1/4	0.283	5	<b>99670</b>	6
1 1/2	1	0.276	5	<b>99675</b>	6
1 1/2	1 1/2	0.443	5	<b>99680</b>	6
2	1	0.459	5	<b>99685</b>	6
2	2	0.719	5	<b>99690</b>	6

**Flanges**



**Viega ProPress adapter flange  
2 - pc  
Smart Connect feature, Zero Lead**  
 - For use with ASTM B88 tubing  
 - Bronze  
 - Press connection  
Components  
 EPDM sealing element  
**Model 2959.5ZL**

P	BP	Wt [lb]	Quantity	Part No	DG
1	4	2.799	1	<b>79680</b>	8
1 1/4	4	3.196	1	<b>79685</b>	8
1 1/2	4	3.857	1	<b>79690</b>	8
2	4	5.466	1	<b>79695</b>	8

BP = bolt pattern



**Viega ProPress XL adapter flange  
2 - pc  
Smart Connect feature**  
 - For use with ASTM B88 tubing  
 - Copper  
 - Press connection  
Components  
 EPDM sealing element  
Note  
 Must be installed with Viega ProPress XL-C rings and V2 actuator.  
**Model 0959.5XL**

P	BP	Wt [lb]	Quantity	Part No	DG
2 1/2	4	6.762	1	<b>20853</b>	8
3	4	8.082	1	<b>20858</b>	8
4	8	11.797	1	<b>20863</b>	8

BP = bolt pattern