

Motorized Vertical Test Stands – MV-275

MV-275 without distance meter
MV-275S with distance meter
Maximum load 275 lbf



- **Combination of screw drive system and high performance brushless motor provides extremely smooth and powerful operation over the entire speed range.**
- **One stand for both compression (push) and tension (pull) tests**
- **Wide speed range: 0.4 – 9.4 in/min (optional speed ranges available)**
- **Clearance 16"**
- **No programming required**
- **Optional digital distance meter and Speed Configurations**



MV-275S with Digital Distance Meter
Force gauges and attachments are sold separately.

MV-275 motorized test stands offer basic force testing. The combination of screw system and state-of-the-art brushless motor provides extremely smooth and powerful operation over the entire speed range.

Speed control, quick return and emergency stop are standard features. The MV-275 accepts any of the standard range Imada force gauges. Optional **digital distance meter** available.

AP-002 Adapter Plate is available to mount most other force gauges to IMADA test stands.

Speed Configurations

Standard Speed	0.4~9.4"/min
Optional High Speed	0.7~23"/min
Optional Low Speed	0.15~4.2"/min

Specify Speed When Ordering

Lexan Safety Shield – LP-99

- **1/4" unbreakable lexan**
- **Helps protect personnel from injury by containing debris during testing**
- **Allows access to the control panel**

The lexan safety shield offers protection to the operators of motorized test stands. Access to the test stand controls is still available through the front of the shield. Made of 1/4" lexan, it is virtually unbreakable and will contain the debris from destructive testing. Helps to prevent accidental injuries. Fits all Imada motorized vertical test stands. Dimensions 16.5" x 15.75" x 31.5"

