

# DIAGNOSTICS, INSPECTION & LOCATING

## Monitors & Recorders

### SeeSnake® CS6 and CS6Pak Digital Recording Monitors

Fast, Efficient Results.

Capture still images and video clips directly to a USB thumbdrive and generate high quality multi-media reports.

Both monitors have the same features and are compatible with all SeeSnake camera reels. The CS6 mounts to the SeeSnake MAX rM200 docking handle for easy transport and storage. The CS6Pak mounts to the Compact2 and can be quickly detached for convenient placement and storage.

The CS6 and CS6Pak have the same great software and reporting capabilities in two distinct form factors.

- One-touch recording – for fast, efficient documentation of inspection jobs.
- Water-resistant keypad – for direct control of essential camera and monitor functions.
- Daylight viewable display – for a crisp, clear in-pipe image.
- SeeSnake HQ Software – to edit, archive, and deliver reports via print, DVD, or online.
- On-screen keyboard – for adding custom job information and text notes.

#### CS6

- Weight (without battery) – 3.6 lb (1.6 kg).
- Length – 14.2" (36 cm).
- Width – 6.5" (16.5 cm).
- Height – 5.1" (13.0 cm).
- Resolution – 640 x 480 (VGA) Color LCD.
- Display – 5.7" Daylight Readable LCD.
- Video – MPEG4 (H.264) 30 FPS.
- Autolog – MPEG4 (H.264) Variable Frame Rate.
- Image – JPEG.
- Audio – Integrated Microphone and Speakers.
- Transfer – USB Thumb Drive .
- Power Source – 18V Advanced Lithium Battery (Optional) or AC a dapter.
- Operating temperature – 14°F to 117°F (-10°C to 47°C).
- Storage temperature – 14°F to 158°F (-10°C to 70°C).
- Relative humidity – 5% to 95%.
- Altitude – 13,120' ( 4,000 m).

#### CS6Pak

- Weight (without battery) – 5.7 lb (2.6 kg).
- Length – 14" (35.6 cm).
- Width – 7.6" (19.3 cm).
- Height – 10.6" (26.9 cm).
- Resolution – 640 x 480 (VGA) Color LCD.
- Display – 5.7" Daylight Readable LCD.
- Video – MPEG4 (H.264) 30 FPS.
- Autolog – MPEG4 (H.264) Variable Frame Rate.
- Image – JPEG.
- Audio – Integrated Microphone and Speakers.
- Transfer – USB Thumb Drive.
- Power Source – 18V Advanced Lithium Battery or AC adapter.
- Operating temperature – 14°F to 117°F (-10°C to 47°C).
- Storage temperature – 14°F to 158°F (-10°C to 70°C).
- Relative humidity – 5% to 95%.
- Altitude – 13,120' (4,000 m).



Catalog No.	Description	Weight	
		lb.	kg
45138	CS6 Digital Recording Monitor	3.6	1.6
45143	CS6 w/2 Batteries and 1 Charger	7.4	3.4
45158	CS6Pak Digital Recording Monitor	5.7	2.6
45163	CS6Pak w/2 Batteries and 1 Charger	9.5	4.3
45363	AC Battery Adapter	1.0	0.5

#### Accessories

Catalog No.	Description	Weight	
		lb.	kg
44848	Set of (1) 2.0Ah Battery & (1) 120V Charger, N. America	2.8	1.30
44853	Set of (2) 2.0Ah Batteries & (1) 120V Charger, N. America	3.8	1.70