



**ViegaPEX Ultra tubing**  
 - PEX  
 - Coil  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
ASTM F876, ASTM F877  
**Model V5003**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¼	100	white	3.200	1	<b>32011</b>	1
¼	500	white	14.000	1	<b>32015</b>	1
⅜	100	white	5.000	1	<b>32001<sup>1</sup></b>	1
⅜	500	white	21.000	1	<b>32005<sup>1</sup></b>	1
⅜	1000	white	42.000	1	<b>32000</b>	1
½	100	white	6.000	1	<b>32021<sup>1</sup></b>	1
½	300	white	17.100	1	<b>32023<sup>1</sup></b>	1
½	500	white	28.000	1	<b>32025<sup>1</sup></b>	1
½	1000	white	55.000	1	<b>32020</b>	1
¾	100	white	11.000	1	<b>32041<sup>1</sup></b>	1
¾	300	white	32.100	1	<b>32043<sup>1</sup></b>	1
¾	500	white	53.000	1	<b>32045<sup>1</sup></b>	1
1	100	white	17.000	1	<b>32061<sup>1</sup></b>	1
1	300	white	51.900	1	<b>32063<sup>1</sup></b>	1
1	500	white	88.000	1	<b>32065</b>	1

<sup>1)</sup> center pull coil



**ViegaPEX Ultra tubing**  
 - PEX  
 - Straight length  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
ASTM F876, ASTM F877  
**Model V5003.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	10	white	0.540	50	<b>33273</b>	1
½	20	white	1.080	50	<b>33020</b>	1
¾	10	white	1.020	25	<b>33276</b>	1
¾	20	white	2.060	25	<b>33045</b>	1
1	20	white	3.420	5	<b>33061</b>	1



**ViegaPEX Ultra tubing**  
 - PEX  
 - Coil  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
ASTM F876, ASTM F877  
**Model V5009**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	100	black	5.500	1	<b>32721</b>	1
½	300	black	16.500	1	<b>32723</b>	1
½	500	black	29.000	1	<b>32725</b>	1



**ViegaPEX Ultra tubing**  
 - PEX  
 - Coil  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
UL listed for NFPA 13D systems, ASTM F876, ASTM F877  
**Model V5009.1**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	100	black	10.500	1	<b>34741</b>	1
¾	300	black	31.500	1	<b>34743</b>	1
¾	500	black	52.500	1	<b>34745</b>	1
1	100	black	17.400	1	<b>34761</b>	1
1	500	black	87.000	1	<b>34765</b>	1
1¼	100	black	25.500	1	<b>34771</b>	1
1¼	300	black	76.500	1	<b>34773</b>	1
1½	100	black	35.400	1	<b>34781</b>	1
2	100	black	63.000	1	<b>32791</b>	1



**ViegaPEX Ultra tubing**  
 - PEX  
 - Straight length  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
ASTM F876, ASTM F877  
**Model V5009.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	20	black	1.100	50	<b>33720</b>	1



**ViegaPEX Ultra tubing**  
 - PEX  
 - Straight length  
Technical Data  
 PEX designation code 5306  
 UV resistance 6 months  
UL listed for NFPA 13D systems, ASTM F876, ASTM F877  
**Model V5009.51**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	20	black	2.100	25	<b>35745</b>	1
1	20	black	3.480	5	<b>35761</b>	1
1¼	20	black	5.100	5	<b>35771</b>	1
1½	20	black	7.060	5	<b>35781</b>	1
2	20	black	12.280	5	<b>33791</b>	1