DIAGNOSTICS, INSPECTION & LOCATING

Monitors & Recorders



CS65 Digital Reporting Monitor

Complete Reporting Solution.

One-touch image and video capture directly to one or two USB drives and the built-in 1 TB hard drive. The CS65 mounts to the SeeSnake Max rM200 for easy transport and storage.

Easily add on-screen titles and annotate captured media with the built-in keyboard and automatically generate high quality multimedia reports.

- One-touch recording for fast, efficient documentation of inspections.
- 1 TB internal hard drive provides ample storage for multiple jobs.
- PhotoTalk[™] pairs audio commentary with an image, in an email-ready file.
- Daylight viewable display for a crisp, clear, in-pipe image.
- · Water-resistant keyboard makes it easy to add onscreen titles and annotate reports.
- HQ Software to edit, archive, and deliver reports via print, DVD, or online.

Specifications

- Weight (without battery) 9.8 lb (4.4 kg).
- Length 15.9" (403 mm).
- Width 12.3" (312 mm).
- Height 9.9" (251 mm).
- Power Source 18V Advanced Lithium Battery or AC Adapter.
- Power Rating 16 to 25 VDC, 30W.
- Operating Temperature 14°F to 122°F (-10°C to 50°C).
- Storage Temperature -4°F to 140°F (-20°C to 60°C).
- Relative Humidity 5% to 95%.
- Altitude 13,120' (4,000 m).
- Display 6.5" (165 mm) Daylight Readable LCD.
- Resolution 640 x 480 VGA.
- Video Format MPEG4 (H.264) 30 FPS.
- Autolog Format MPEG4 (H.264) Low, Variable Frame Rate Decreased File Size.
- Image Format JPEG.
- Audio Integrated Microphone and Speakers.
- Transfer USB Drive.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
48123	CS65	CS65 Digital Reporting Monitor	9.5	4.3
48133	CS65	CS65 w/2 Batteries and 1 Charger	13.3	6.0

12.17