

## ELECTRICAL

# Cable Cutters



### No. 1380 Cable Cutter

- The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 1<sup>3</sup>/<sub>8</sub>" diameter and 750 MCM\*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

\*Not intended for cutting steel or ACSR cable.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
83350	1380	Aluminum and Copper Cable through 1 <sup>3</sup> / <sub>8</sub> Diameter and 750 MCM	4 <sup>1</sup> / <sub>2</sub>	2.0

# Cable Trimmers



### No. 87 ACSR Cable Trimmer

RIDGID® No. 87 ACSR Cable Trimmer for fast, accurate cable splice preparation.

- Trims 85 sizes of ACSR cable from 8 AWG to 1,780,000 circular mils (C.M.).
- Bushings for 9 popular cable sizes from 1/0 AWG through 1,780,000 C.M. available from stock.
- The operation of the tool is similar to that of a conventional tubing cutter.
- The bushing holder, cutter and handy carrying case are sold as one unit.
- Case contains storage sockets for 11 bushings. Twelfth bushing is stored in holder.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
54135	87	ACSR Cable Trimmer, includes Bushing Holder, Cutter, and Carrying Case	9 <sup>1</sup> / <sub>2</sub>	4.30
54270	E-4695	Cutter Wheel	1	0.02

### Standard Equipment

Catalog No.	Model No.	Bushing No.	A.W.G. or C.M.	No. of Strands
54440	—	E-5761	2/0	6/1
54445	—	E-5762	2/0	6/1
54450	—	E-5763	4/0	6/1
54465	—	E-5766	266,800	26/7
54480	—	E-5769	336,400	26/7
54500	—	E-5773	397,500	26/7
54520	—	E-5777	477,000	26/7
54540	—	E-5781	556,500	26/7
54575	—	E-5788	636,000	54/7 24/7