

**Tubing**



**ViegaPEX Barrier tubing**

- PEX
- Coil
- Oxygen diffusion barrier, protective outer layer

Technical Data

PEX designation code 5306  
 Chlorine resistance ratings CL5  
 UV resistance 6 months

ASTM F876, ASTM F877, NSF 61, CAN/ULC S101, CAN/ULC S102.2

**Model 2802US**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
5/16	250	black with stripe	9.000	1	11400	4
5/16	1000	black with stripe	34.000	1	11405	4
5/16	4000	black with stripe	136.000	1	11410	4
3/8	300	black with stripe	12.900	1	11415	4
3/8	1200	black with stripe	51.600	1	11418	4
3/8	2400	black with stripe	103.200	1	11420	4
1/2	250	black with stripe	10.750	1	11428	4
1/2	300	black with stripe	17.100	1	11425	4
1/2	400	black with stripe	23.200	1	11430	4
1/2	500	black with stripe	29.000	1	11427	4
1/2	1000	black with stripe	58.000	1	11436	4
1/2	1200	black with stripe	68.400	1	11435	4
1/2	2000	black with stripe	112.000	1	11440	4
5/8	500	black with stripe	40.000	1	11445	4
5/8	1500	black with stripe	118.500	1	11450	4
3/4	150	black with stripe	16.050	1	11455	4
3/4	300	black with stripe	32.400	1	11457	4
3/4	500	black with stripe	56.500	1	11458	4
3/4	800	black with stripe	86.400	1	11460	4
3/4	1000	black with stripe	108.000	1	11462	4
1	150	black with stripe	27.000	1	11465	4
1	500	black with stripe	88.000	1	11470	4
1 1/4	100	black with stripe	27.000	1	11475	4
1 1/2	100	black with stripe	36.500	1	11480	4
2	100	black with stripe	60.300	1	11485	4



**ViegaPEX Barrier tubing**

- PEX
- Straight length
- Oxygen diffusion barrier, protective outer layer

Technical Data

PEX designation code 5306  
 Chlorine resistance ratings CL5  
 UV resistance 6 months

ASTM F876, ASTM F877, NSF 61, CAN/ULC S101, CAN/ULC S102.2

**Model 2803US**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	20	black with stripe	2.100	25	11500	4
1	20	black with stripe	3.500	5	11505	4
1 1/4	20	black with stripe	5.280	5	11510	4
1 1/2	20	black with stripe	7.400	5	11515	4
2	20	black with stripe	12.280	5	11520	4



**Viega FostaPEX tubing**

- Only for Viega PEX Press fittings
- PEX/AL/PE
- Coil
- Form stable

Technical Data

PEX designation code 5306

Note

UV resistance is 6 months for inner PEX core and extended with aluminum coating <sup>1)</sup> center pull coil

ASTM F876, ASTM F877

**Model 2805US**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	150	silver	15.000	1	35020 <sup>1</sup>	6
1/2	300	silver	30.000	1	35019 <sup>1</sup>	6
1/2	400	silver	38.000	1	35021 <sup>1</sup>	6
5/8	150	silver	21.000	1	35030 <sup>1</sup>	4
5/8	400	silver	56.000	1	35031 <sup>1</sup>	4
3/4	150	silver	24.000	1	35040 <sup>1</sup>	6
1	150	silver	39.000	1	35060 <sup>1</sup>	6