

2 ■ CUTTING / SAWING / CORE DRILLING / REAMING / GAUGING

Description	Ø max. mm	V 150+	V 250	V 350	Kg	Ref.
Sharpening stone	-	ok	ok	ok	2,000	050175

0500 : Manual Water Pump

For Core Drills:
V 150+ / V 250 / V 350 / V 130 / V 200 / V 300.

Capacity: 10 L.
Max service pressure 6 bar, with safety valve.
Steel tank with polyester coating.

Kg	Ref.
6,000	050049



0500 : Electrical Water Pump

For core drills:
V 150+ / V 250 / V 350 / V 130 / V 200 / V 300.

Easy, convenient and economical system, to supply the core drill with water. It is the ideal product to solve the damaging of the core bits due to insufficient water-supplying.
Warning : Always keep the pump horizontally.
Water suction max. height: 1.8 m.

Size mm	Voltage V	Kg	Ref.
340 x 190 x 280	220	1,640	050055



STEEL AND CAST IRON PIPE CUTTER

2101 : Steel Pipe Cutter

Max thickness: 5 mm.

For quickly cutting steel pipes (gas- API-etc...) cleanly and squarely.
Also cuts stainless steel pipes (> 2 mm thick) with cutting wheels 210123 and grey cast iron with cutting wheels 210122.



A pipe "	A pipe mm	L mm	H mm	E maxi mm	Kg	Ref.
1/8 - 1.1/4	10 - 42	310	118	5	1,740	210110
1/2 - 2	21 - 60	400	150	5	3,020	210120
3/4 - 3	27 - 90	460	177	5	4,220	210130



Virax certified ISO 14001 and OHSAS 18001 since 2009