
RADIAL CRIMPING

2529 : Viper® i10 Manual Hydraulic Press Fitting Tool



Virax has jaws and inserts for the majority of crimping systems available on the market.

Capacity

PER, PEX, PB, and PEX/AL/PEX pipes Ø 12 to Ø 20 mm.

PEX/AL/PEX pipes: Ø 12 to Ø 20 mm.

Not adapted for copper, stainless steel and steel tube.

Ultra high-performance hydraulic system, guarantees a perfect, long-lasting crimp. Comfort of use: ergonomic and well balanced for effortless crimping, best weight-to-power ratio on market.

Head with autocatalytic phosphorous nickel plating on steel (anticorrosion protection).

Wide choice of inserts: Virax has inserts for the majority of crimping systems available on the market.

Size: 255 x 170 x 55 mm.

Supplied in a case (without inserts).

WARNING: selected inserts only.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.





	Description	Size mm	Crimping force kN	Kg	Ref.
2	Viper® i10	390 x 325 x 100	34-40	2,760	252900

2530 : Viper® P10 Manual Hydraulic Press Fitting Tool



180° pivoting head: for ease of use in all situations. Audible "click" when crimping complete.

Capacity

PER, PEX, PB, and PEX/AL/PEX pipes Ø 12 to Ø 63 mm. PEX/AL/PEX pipes: Ø 12 to Ø 63 mm. Copper, stainless steel and mild steel pipes: Ø 12 to Ø 54 mm. Ultra high-performance hydraulic system, guarantees a perfect, long-lasting crimp. Comfort of use: ergonomic and well balanced for effortless crimping. 2-speed hydraulic system for quicker crimping. Quick locking axles. Discharge lever piston return on the moving handle. Takes all crimping press fittings available on the market. Can be used with all currently available crimping jaws. Size: 515 x 115 x 70 mm.

Supplied in a case (without inserts).

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.



	Description	Size mm	Crimping force kN	Kg	Ref.
i.	Viper® P10	670 x 200 x 100	32-35	3,240	253010



Virax is on Twitter!

@ViraxOfficial