

Screen Material

- MaxWhite FG front projection material
- 1.1 Gain with wide 180° viewing angle
- Black masking borders enhance picture contrast
- Flame Retardant: Complies with NFPA 701 Standards
- Active 3D and 4K Ultra HD Ready

Housing Finish and Installation

- Aluminum housing with white finish is slim yet strong and moisture resistant
- Concealed in-ceiling front projection screen for multi-use rooms
- Below and above ceiling access installation design
- Installation kit included

Control System

- Internal Radio Frequency and Infrared receivers with IR and RF remotes included
- Low voltage 3-way position wall switch
- Optional in-wall up/down switch, wireless 5-12 volt trigger
- RJ45 port allows 3rd party control systems integration

Quality and Reliability

- Tubular motor allows swift operation with a superior weight tolerance and operational lifespan
- 2-year warranty
- 3-year warranty for ENR-G (Educational, Non-profit, Religious or Government/Military) - US only

Certified

GREENGUARD® and GREENGUARD® Gold Certified | UL 2818

Evanesce B Series

Model	Nominal Diagonal	View Width (in/mm)	View Height (in/mm)
EB100VW2-E8	100"(4:3)	80.0/2032.0	60.0/1524.0
EB120VW2-E8	120"(4:3)	96.0/2438.4	72.0/1828.8
EB100HW2-E8	100" (16:9)	87.2/2049.0	49.0/1152.0
EB110HW2-E8	110"(16:9)	96.0/2438.4	54.0/1371.6
EB120HW2-E8	120"(16:9)	104.6/2458.0	58.9/1384.0

4:3 | 16:9 | 16:10 | 2.35:1



Features:

- Available in diagonal sizes ranging from 90"-132"
- Four aspect ratios to choose from, 4:3, 16:9, 16:10 & 2.35:1
- Disappearing in-ceiling design for non-dedicated media rooms
- Integrated ceiling projection screen ships fully assembled, ready to install

Screen Material:

- MaxWhite FG 1.1 gain black backed matte white screen material
- Available in AcousticPro UHD Sound Transparent Material, 1.0 Gain, Moiré-free

Housing Finish and Installation:

Aluminum Housing with enamel coating is moisture resistant

Control System:

- Internal Radio Frequency/Infrared receivers with IR, RF remotes included
- Low voltage 3-way wall switch included
- 5-12Volt trigger included to synchronize screen operation with the projector's power cycle
- Optional In-wall up/down switch

Quality and Reliability:

- Standard 2-year parts and labor warranty
- 3-year warranty for ENR-G (Educational, Non-profit, Religious or Government/Military) - US only
- FCC, CE, CB GOSTCE & ISO9001:2008 Certified
- GREENGUARD® and GREENGUARD® Gold Certified | UL 2818

Evanesce

4:3 | 16:9 | 16:10 | 2.35:1

Evanesce Series

Model	Nominal Diagonal	View Width (in/mm)	View Height (in/mm)
IHome106VW2-E18	106"(4:3)	84.8/2153.9	63.6/1615.4
IHome126VW2-E8	126"(4:3)	100.8/2560.3	75.6/1920.2
IHome90HW2-E24	90"(16:9)	78.4/1992.5	44.1/1120.8
IHome106HW2-E18	106"(16:9)	92.4/2346.7	52.0/1320.1
IHome112HW2-E16	112"(16:9)	97.6/2479.5	54.9/1394.8
IHome126HW2-E20	126"(16:9)	109.8/2789.5	61.8/1569.2
IHome100XW2-E24	100(16:10)	84.8/2153.9	53.0/1346.2
IHome114XW2-E20	114"(16:10)	96.7/2455.5	60.4/1534.7
IHome120XW2-E18	120"(16:10)	101.8/2584.7	63.6/1615.4
IHome132XW2-E12	132"(16:10)	111.9/2630.0	70.0/1644.0
IHome110C-E24	110"(2.35:1)	101.2/2570.5	43.1/1094.7
IHome122C-E22	122"(2.35:1)	112.4/3312.0	47.8/1215.0



Evanesce Tab-Tension B

16:9



Screen Material

- CineWhite tensioned front projection material
- 1.1 Gain with 180° viewing angle
- Black backed screen material
- Tab-tension system provides a flat surface with no tab impressions
- Active 3D and 4K Ultra HD Ready

Housing Finish and Installation

- Aluminum housing with white finish is slim yet strong and moisture resistant
- Concealed in-ceiling front projection screen for multi-use rooms
- Below and above ceiling access installation design
- Installation kit included
- RJ45 port allows 3rd party control systems integration

Control System

- Internal Radio Frequency and Infrared receivers with IR and RF remotes included
- Low voltage 3-way position wall switch
- Optional in-wall up/down switch, wireless 5-12 volt trigger
- RJ45 port allows 3rd party control systems integration

Quality and Reliability

- Tubular motor allows swift operation with a superior weight tolerance and operational lifespan
- 2-year warranty
- 3-year warranty for ENR-G (Educational, Non-profit, Religious or Government/Military) - US only

Evanesce Tab-Tension B

16:9

Evanesce Tab-Tension B Series

Model	Nominal Diagonal	View Width (in/mm)	View Height (in/mm)
ETB100HW2-E8	100" (16:9)	87.2/2049.0	49.0/1152.0
ETB110HW2-E8	110" (16:9)	95.9/2436.0	53.9/1369.0
ETB120HW2-E8	120" (16:9)	104.6/2458.0	58.9/1384.0

Evanesce Tab-Tension

4:3 16:9 16:10



Screen Material

- Award winning CineWhite 1.1 Gain black backed matte white screen material
- 180° wide-viewing angle
- Tab-tension cords provide uniform flatness on entire projection surface
- Standard 8" top drop
- Available in various diagonal sizes and aspect ratios
- Active 3D and 4K Ultra HD Ready

Housing Finish and Installation

- Disappearing in-ceiling design for non-dedicated media rooms
- Integrated ceiling projection screen ships fully assembled, ready to install
- Aluminum housing with white finish is strong and moisture resistant
- Above and below ceiling installation kit included

Control System

- Internal Radio Frequency/Infrared receivers with IR, RF remotes included
- Low voltage 3-way wall switch and in-wall RJ45 module included
- Standard 5-12 volt trigger to synchronize screen operation with the projector's power cycle
- Optional in-wall up/down switch (part# ZIW-W)

Quality and Reliability

- 2-year manufacturer's warranty
- FCC, CE, CB GOSTCE & ISO9001:2008

Evanesce Tab-Tension

4:3 | 16:9 | 16:10 |

Evanesce Tab-Tension Series

Model	Nominal Diagonal	View Width (in/mm)	View Height (in/mm)
ITE100VW2-E8	100"(4:3)	80.0/2032.0	60.0/1524.0
ITE120VW2-E8	120"(4:3)	96.0/2438.0	72.0/1829.0
ITE100HW2-E8	100"(16:9)	87.2/2215.0	49.1/1247.0
ITE106HW2-E8	106"(16:9)	92.4/2347.0	52.0/1321.0
ITE120HW2-E8	121"(16:9)	104.6/2657.0	58.8/1494.0
ITE135HW2-E8	135"(16:9)	117.7/2990.0	66.2/1681.0
ITE108XW2-E8	108"(16:10)	91.6/2326.0	57.2/1454.0
ITE114XW2-E8	114"(16:10)	96.6/2454.0	60.4/1534.0
ITE126XW2-E8	126"(16:10)	106.8/2713.0	66.8/1695.0



Evanesce Plus



Screen Material

- MaxWhite Fiberglass front projection material with black backing
- 1.1 Gain with wide 180° viewing angle
- Black masking borders enhance picture contrast
- Flame Retardant: Complies with NFPA 701 Standards
- Active 3D and 4K Ultra HD Ready

Housing Finish and Installation

- Extra wide and heavy-duty aluminum housing is strong and moisture resistant
- Concealed in-ceiling front projection screen for large size rooms
- Installation kit included for above ceiling access

Control System

- Internal Radio Frequency and Infrared receivers with IR and RF remotes included
- Low voltage 3-way position wall switch
- Optional in-wall up/down switch, wireless 5-12 volt trigger
- RJ45 port allows 3rd party control systems integration

Quality and Reliability

- Tubular motor allows swift operation with a superior weight tolerance and operational lifespan
- 2-year warranty
- 3-year warranty for ENR-G (Educational, Non-profit, Religious or Government/Military) - US only

Certified

GREENGUARD® and GREENGUARD® Gold Certified | UL 2818

Evanesce Plus

4:3 16:9

Evanesce Plus Series

Model	Nominal Diagonal	View Width (in/mm)	View Height (in/mm)
IHome150VW2-E12	150"(4:3)	120.0/3048.0	90.0/2286.0
IHome180VW2-E12	180"(4:3)	144.0/3657.6	108.0/2743.2
IHome200VW2-E8	200"(4:3)	160.0/4064.0	120.0/3048.0
IHome150HW2-E12	150" (16:9)	130.7/3319.8	73.6/1869.4
IHome180HW2-E12	180" (16:9)	156.9/3985.3	88.3/2242.8
IHome200HW2-E6	200" (16:9)	174.0/4419.6	98.0/2489.2

