

Description	Standard / Option	Copper tube ext. Ø mm	Copper tube ext. Ø "	Iron tube ext. Ø ext. "	Kg	Ref.
2 x Adaptors GR III	Supplied with Siberia®	14 / 15	-	1/4	0,345	221027
2 x Adaptors GR IV	Supplied with Siberia®	16	5/8	-	0,340	221028
2 x Adaptors GR V	Supplied with Siberia®	18	-	3/8	0,335	221029
2 x Adaptors GR VI	Option	20	3/8	-	0,320	221030
2 x Adaptors GR VII	Supplied with Siberia®	22	7/8	1/2	0,290	221031
2 x Adaptors GR VIII	Option	-	1	-	0,280	221032
2 x Adaptors GR A	Supplied with Siberia®	28	-	3/4	0,675	221033
2 x Adaptors GR B	Option	-	1.1/8	-	0,695	221034
2 x Adaptors GR C	Option	32	1.1/4	-	0,645	221035
2 x Adaptors GR D	Supplied with Siberia®	35	1.3/8	1	0,575	221036
2 x Adaptors GR F	Option	-	-	1.1/2	0,315	221038
2 x Adaptors GR E	Supplied with Siberia®	42	-	1.1/4	0,430	221037
2 x Adaptors GR G	Option	54	2.1/8	-	0,190	221039

GAS THIGHTNESS CONTROLLER

2620 : Gas Tightness Controller



Very compact: holding in only one hand and being able to be transported easily.

Strong: very resistant composite material.

Ergonomic: easily transportable in its storage bag.

Modern design.

Checks the tightness seal of a gas installation in a pressure less than 50 mbar. its automatic limiting device of pressure avoids any risk of error.



Dimensions mm: 165 x 80 x 80.

Light: 1.280 kg.

Supplied with:

- 1 coupling hose,
- brass couplings: 1/2 G female, 7/8 G male, propan 20/150 male,
- box of seals,
- 1,5 V battery (LR6/AA),
- protective carrying bag.



Pression mbar	Coupling "	Resolution mbar	Kg	Ref.
0 to 60	1 fitting for gas cooker, 1/2 G female, 7/8 G male gasmeter outlet connection, 1 male propan fitting 20/150	1	1,280	262080



Virax, Partner of WorldSkills France

As a partner of the Plumbing and Roofing pole since 2012, our objective is to promote learning and professional tuition of young people below 23 years old. Apprentices can thus express their talent and invest in their future while promoting their business.