2518: Former and Counter-Former for Eurostem® II








Туре	Pipe O.D. mm	Pipe O.D. "	Bending radius	Kg	Ref.
Formers and counter-former	10	ā	40	0,260	251810
Former	12	9	45	0,220	251812
Former	14	-	50	0,290	251814
Former	15		55	0,325	251815
Former	16	¥	60	0,380	251816
Former	18	*	70	0,590	251818
Formers and counter-former	20		77	0,930	251820
Former	22	¥	77	0,710	251822
Formers and counter-former	25	-	98	1,720	251825
Formers and counter-former *	26	į.	98	1,700	251826*
Formers and counter-former	28	-	98	1,560	251828
Formers and counter-former	28	-	112	1,820	251829**
ormers and counter-former *	32	8	112	1,620	251831*
Formers and counter-former	*	3/8	40	0,270	251860
Former		1/2	45	0,240	251863
Former	8	5/8	55	0,320	251866
Former	ž.	3/4	70	0,600	251869
Former	*	7/8	77	0,690	251872
Formers and counter-former	25	1.1/8	98	1,600	251879
Counter-former	12/15	*	*	0,055	251832
Counter-former	14/16	-		0,065	251833
Counter-former	18/22	2	<u>~</u>	0,085	251834
Counter-former		1/2 - 5/8		0,050	251882
Counter-former		3/4 - 7/8		0,080	251883

2518: Concentric Radius Former for Eurostem® II

Former with special bending radius for parallel working on double collars.

Ø mm	Bending radius	Kg	Ref.	
12	75	0,410	251835	
14	80	0,580	251836	
16	90	0,780	251837	
18	105	0,960	251838	
22	120	1,380	251839	





^{*} For PEX/AL/PEX pipes.
** For stainless steel pipes Ø 28 x 1.2 mm.