

4 CONNECTION / ASSEMBLY

CUTTING OIL

1101 - 1102 : Mineral Cutting Oil

Specially designed for manual and powered threading. With its very high lubricating ability, Virax cutting oil ensures better quality threads and lengthens the service life of both dies and machines.

New, improved blend. Water emulsifiable. Odourless.

WARNING : It is essential to rinse off the oil with detergent when used on drinking water circuits.

L	Packaging	Kg	Ref.
1	Container	0,985	110101
5	Container	4,860	110105
1	Box of 12 containers	12,430	110112
500 ml	Spray can	0,620	110200
500 ml	Box of 12 spray cans	6,900	110202



1105 : Stainless Steel Mineral Cutting Oil

Specially designed for manual and powered threading. With its very high lubricating ability, Virax cutting oil ensures better quality threads and lengthens the service life of both dies and machines.

Water emulsifiable.

WARNING: Must be rinsed with detergent when used on drinking water circuits.

L	Packaging	Kg	Ref.
5	Container	4,600	110505



1106 : Synthetic Threading Oil



Special threading on drinking water circuits.

Odourless: For a better user comfort.

High technical performances: Threading couple and tools durability are improved.

Acceptable for fresh water: specially done to thread drinkable water pipings, all the oil is eliminated by rinsing it out.

DVGW-Arbeitsblatt W 521 n° DW-0201BR5779.

Dynamic viscosity at -10°C : < 250 mPa s.

Use it without diluting.

L	Packaging	Kg	Ref.
5	Container	5,720	110605



Virax certified ISO 14001 and OHSAS 18001 since 2009