



The World's No. 1 Brand of Air-sampling Smoke Detector



7 Reasons for VESDA

1

When business continuity is paramount

Is uptime a key business goal? Is service provision critical?

VESDA by Xtralis very early warning smoke detectors provide the earliest warning of a potential fire that buys time to investigate, intervene and potentially avoid business disruption in addition to the damage, downtime and cost of a suppression release. Such early warning is critical for:

- Telecommunications facilities
- Server rooms
- Financial data centers
- Utilities
- Clean rooms
- Power generation facilities

2

When smoke is difficult to detect

Is high airflow diluting smoke, preventing it from reaching the ceiling so it can be detected? Is the smoke being trapped in ducts, pockets or voids? Is smoke stratifying into a mushroom cloud below a high ceiling, making it difficult to detect?

VESDA sampling points can be placed at the return air grill or in equipment cabinets to detect smoke as it is carried by the air. In large, open spaces, sampling points for VESDA detectors can be placed where smoke goes — often some distance below ceiling level. Suitable for:

- Server rooms
- Clean rooms
- Telecommunications facilities
- Warehouses
- Atriums
- Indoor stadiums
- Theaters
- Convention centers

3

When maintenance access is difficult

Is the area to be protected inaccessible? Does maintenance on current fire protection systems cause disruptions and inconvenience your business?

VESDA detectors can be mounted in accessible locations to enable easy maintenance. Only the sampling pipe network is placed in the inaccessible area. Ideal for:

- Ceiling voids and sub-floor spaces
- Prisons and detention facilities
- Elevator shafts
- Ducts
- Production areas



4

When unobtrusive detection is required

Is it important to preserve the internal design/decoration of the building? Is vandalism a problem with the current smoke detection system?

A VESDA system can be installed with tiny capillary sampling tubes, which are barely discernible to the human eye. The detectors can be placed in a cupboard or utility area. Great for:

- Modern offices
- Cathedrals
- Art galleries and museums
- Heritage buildings
- Prisons and detention centers
- Prestigious residences

5

When evacuation is a challenge

Will the building be open to the general public? Will it house people who need extra help during an evacuation? Is evacuation difficult due to crowds or limited exits? What is the business impact of an evacuation?

The very early warning that a VESDA system provides allows the maximum time for evacuation. This is critical for:

- Shopping centers
- Stadiums
- Heritage buildings
- Hospitals
- Underground tunnels
- Facilities for children and the elderly

6

When environmental conditions are difficult

Is poor air quality or are extreme temperatures present in the area to be protected?

VESDA detectors feature dual-stage filtration to ensure they continue to function reliably in dirty environments. The detectors can be installed elsewhere, with only the sampling pipes in the extreme environment. The sampled air can be filtered, warmed or cooled before reaching the detector. Ideal for:

- Power stations
- Public transport
- Paper and saw mills
- Cold stores
- Mines
- Automotive operations
- Manufacturing facilities
- Hazardous areas (Factory Mutual Class 1 Div 2)

7

When suppression systems are present

Is suppression release costly and disruptive?

The very early warning provided by a VESDA system allows early intervention to prevent suppression releases. The multiple warning levels of a VESDA system can be used to trigger different responses at different stages of a fire — from controlling air conditioning to initiating a suppression release. Applicable for:

- Communications hubs
- Command stations
- Server rooms
- Switch rooms




VESDA by Xtralis Air-sampling Smoke Detection (ASD)

The World's No. 1 ASD Brand

VESDA by Xtralis very early warning smoke detection solutions provide the earliest possible warning of an impending fire hazard. VESDA buys time to investigate an alarm and initiate an appropriate response to prevent injury, property damage or business disruption. And because VESDA has the industry's widest sensitivity range and multi-level warnings, even minute levels of smoke can be detected before a fire has time to escalate.

As the No. 1 ASD brand specified by fire professionals around the world, VESDA is synonymous with reliable, high-performance fire detection.




This diagram shows the progression of a fire over time. Note that the incipient stage of a fire provides the widest window of opportunity to detect and control the spread. VESDA detectors can be configured to generate multiple alarms within the incipient stage. They also can be configured to generate an additional alarm (Fire 2) in the advanced stages of a fire. This feature is unique to VESDA and takes advantage of its wide sensitivity range that enables one detector to monitor the entire progression of a fire.

How VESDA Works

VESDA works by continuously drawing air into a distributed pipe network via a high-efficiency aspirator. The air sample then passes through a dual-stage filter. The first stage removes dust and dirt from the air sample before it enters the laser detection chamber. The second, ultra-fine stage provides an additional clean-air supply to keep the detector's optical surfaces free from contamination, ensuring stable calibration and long detector life as well as minimizing nuisance alarms.

From the filter, the air sample goes through the calibrated detection chamber where it is exposed to a laser light source. When smoke is present, light is scattered within the detection chamber and is instantly identified by the highly sensitive receiver system. The signal is then processed and presented via a bar-graph display, alarm threshold indicators and/or graphic display. VESDA detectors are able to communicate this information to a fire alarm control panel, a software management system, or a building management system via relays or a High Level Interface (HLI).



VESDA by Xtralis Product Range

VESDA VFT

The VESDA VFT is a unique and versatile high-sensitivity ASD that is able to pinpoint the source of incipient smoke to speed response, enhance investigation, and minimize business disruption and downtime. This advanced detector provides intelligent addressability to identify up to 15 protected areas via microbore air-sampling tubes.

VESDA VLP (LaserPLUS™)

The VESDA VLP is the most popular detector in the VESDA by Xtralis product range. Like all VESDA ASDs, it detects fire at the earliest possible stage and reliably measures very low to extremely high concentrations of smoke. It has the world's widest sensitivity range of 0.005 to 20% obs/m (0.0015 to 6% obs/ft). VESDA VLP supports four configurable alarms (Alert, Action, Fire 1 and Fire 2) and protects areas up to 2,000 square meters (20,000 square feet).

VESDA VLS (LaserSCANNER™)

The VESDA VLS locates the origin of smoke by identifying the first sector (pipe) with the highest level of smoke and then continues to sample air from all sectors to monitor fire growth. The VESDA VLS also provides four alarm levels for each individual pipe (Alert, Action, Fire 1 and Fire 2) and provides individual pipe addressability and settings. It protects areas up to 2,000 square meters (20,000 square feet).

VESDA VLC (LaserCOMPACT™)

The VESDA VLC offers cost-effective protection of single environments and small areas. It offers the same wide sensitivity range as the VESDA VLP and VESDA VLS — 0.005 to 20% obs/m (0.0015 to 6% obs/ft). The VESDA VLC supports three configurable alarm levels (Alert, Pre-Alarm and Fire) and comes in two versions. One version interfaces via relays only (RO) and the other across either relays or VESDAnet (VN). In addition, an explosion-proof version of the VN VLC is available for the protection of hazardous areas.

VESDA VLF (LaserFOCUS™)

The VESDA VLF delivers the most advanced and cost-effective air-sampling smoke detection technology for small environments. The VESDA VLF-250 model protects areas up to 250 square meters (2,500 square feet), and the VESDA VLF-500 model covers up to 500 square meters (5,000 square feet). In addition to the features found in all Xtralis Laser products, VESDA VLF provides a new range of features and built-in intelligence for quick installation, commissioning and servicing.

VESDA VLT (LaserTEKNIC™)

The VESDA VLT enables Original Equipment Manufacturers to offer the benefits of VESDA by Xtralis very early warning smoke detection in their products with little development investment.

Remote Displays and Programmers

The VESDA display module monitors and reports the status of a detector, providing visual representation of smoke levels along with all alarm and fault conditions. For monitoring convenience, multiple displays can be associated with a single detector.

The menu-driven VESDA Programmer allows the user to conveniently configure, commission and maintain the VESDA system, as well as program each individual detector. Only one programmer is needed to support the entire network.

Display and programmer modules can be mounted in a detector unit separately (connected via VESDAnet), in a single remote mounting box, or in a 19-inch sub rack.



VFT



VLP



VLS



VLC



Ex d



VLF



VLT



VESDA by Xtralis Product Range

VESDAnet™


VESDAnet is a comprehensive, fault-tolerant, “closed,” two-wire communications loop that links VESDA detectors, displays, programmers and remote units on a daisy-chained loop. VESDAnet enables a number of units to be programmed together from one or more locations and automatically detects communication failures.

It also easily interfaces with systems external to the network, such as intelligent fire alarm panels and building management systems.

VESDA Pipe

A key element in the performance of a VESDA by Xtralis ASD system is the network of sampling pipes that actively transports air from a protected area to the detector. Xtralis offers an extensive range of pipe and fittings to suit all application needs, ensuring a quality system is installed every time.

Some pipes and fittings are not available in certain countries. Please check with an Xtralis office before you order.



Both VSC and ASPIRE2 are compatible with all detectors in the VESDA product line.

Software

VSM™

The VSM software package allows the user to monitor, configure and control a VESDA by Xtralis system from a central location via a VESDAnet communication loop or directly to VESDA detectors. Real-time and historical events for a single detector or multiple networks of detectors can be collected over a local- or wide-area network. The data then can be processed and presented in either report or graphical format — even graphically on site floor plans.

VSC™

The VSC software package can be used to configure, install, commission and maintain the standard range of VESDA ASDs. The software provides high-level programming flexibility through its on-line and off-line configuration capabilities. Rapid diagnostic abilities, concurrent configuration views, compare/merge functionality, and simultaneous smoke-trend graphing of multiple detectors are additional features designed to simplify operation and installation setup.

VESDA ASPIRE2™

VESDA ASPIRE2 is the latest version of VESDA sampling pipe network design and modeling software. It aids in the design and evaluation process for basic to very complex pipe-network layouts. Key features, such as design wizards, 3-D isometric views, an automated design verification process, and a new AutoBalance capability, ensure that a tailored pipe layout is easily achieved. The Installation Data Pack (IDP) generates a series of reports with the parameters, required materials and expected system performance so installation and commissioning engineers receive this information clearly.



Detector Configurations

Features						
	VFT-15	VLS	VLP	VLC VESDAnet (VN)	VLC Relays Only(RO)	VLF 250/500
Worldwide Approvals	Vds, UL, FM, CSFM	LPC, VdS, AFNOR, UL, ULC, UL268A (in-duct application), FM, NY-MEA, CSFM, ActivFire, CFE.				
Hazardous Area Approval (FM Class 1, Div 2, Groups A, B, C, D)	No	No	Yes	Yes	Yes	Yes
Sensitivity Range	0.001 to 20% obs/m (0.0003 to 6.0% obs/ft)	0.005 to 20% obs/m (0.0015 to 6% obs/ft)				0.025 to 20% obs/m (0.008 to 6.4% obs/ft)
Two-stage Filter	Yes	Yes	Yes	Yes	Yes	Yes
Area Coverage (Maximum)	1,500 m ² (15,000 ft ²) (across 15 sectors)	2,000 m ² (20,000 ft ²) (across 4 sectors)	2,000 m ² (20,000 ft ²)	800 m ² (8,000 ft ²)	800 m ² (8,000 ft ²)	250/500 m ² (2,500/5,000 ft ²)
Multiple Pipe Addressability	Up to 15	Up to 4	No	No	No	No
Total Number of Alarm Thresholds	120 (Day/Night)	32 (Day/Night)	8 (Day/Night)	3	3	8 (Day/Night)
Relay Outputs	5 (Expands to 21)	7 or 12 relays	7	3	3	3 (Expands to 6)
On-board Memory (Max. Events)	Up to 20,000	18,000	18,000	12,000	12,000	18,000
Flow Sensor Circuit (one per pipe inlet)	1 + 1 in chamber	4	4	1	1	1
AutoLearn™ (automatically adjusts system to environment)	No	Yes	Yes	Yes	Yes	AutoLearn Smoke™ AutoLearn Flow™
Supported by ASPIRE2™ Pipe Network Design Software	Yes (transport times only) Predefined networks	Yes	Yes	Yes	Yes	Yes
Maximum No. of Holes	15	60	100	40	40	12/24
Bar Graph/Indicator LED	Yes	Local or Remote (20-segment bargraph display)	Local or Remote (20-segment bargraph display)	Local (5 on-board LEDs, remote 20-segment bargraph display)	Local (5 on-board LEDs)	Local (7 on-board LEDs, 10-segment circular display)
Programming Tools - On-board Programming Module - Portable Programmer - PC Software (VSC, VSM) via VESDAnet (when the detectors are connected on the VESDA network)	On-board programmer and PC software (VSC/VSM4)	Yes	Yes	Yes	Programmed via RS232 direct connection to PC using VSC	Programmed via RS232 direct connection to PC using VSC
VESDAnet						
Max. No. of Devices/Detectors per Loop	N/A	200/100	200/100	200/100	N/A	200/100 (with VN Card)
Max. Distance between Devices	N/A	1,300 m (4,000 ft)	1,300 m (4,000 ft)	1,300 m (4,000 ft)	N/A	1,300 m (4,000 ft) (with VN Card)
Computer-based Management via VSM	Yes	Yes	Yes	Yes	No	Yes (with VN Card)
Remote Relay Modules - 7-relay version - 12-relay version	N/A	(Part No.) VRT-501 VRT-900	VRT-500 N/A	VRT-500 N/A	N/A	VRT-500 N/A
Compatible Remote Bar-graph Displays - Display, 7-relays - Display, 12-relays - Display, no relays	N/A	(Part No.) VRT-400 VRT-800 VRT-700	VRT-200 N/A VRT-600	VRT-J00 N/A VRT-K00	N/A N/A N/A	VRT-V00 N/A VRT-W00

The full range of VESDA by Xtralis ASDs are EN 54-20 tested and approved.

About Us

Xtralis is a leading global provider of powerful, early warning fire detection and security solutions that prevent disasters by giving users time to respond before life, critical infrastructure or business continuity is compromised. We protect more than 40,000 customer sites in 100 countries, including billions in assets belonging to the world's top governments and businesses. Our solutions include VESDA® by Xtralis – very early warning fire detection, ICAM® by Xtralis – flexible fire and environmental monitoring, ADPRO® by Xtralis – outdoor and enterprise security, and ASIM® by Xtralis – traffic detection.

Xtralis is the leader in very early warning fire detection and invented the VESDA air-sampling smoke detector (ASD), the world's No. 1 ASD brand. Customers worldwide rely on VESDA by Xtralis when business continuity is imperative, environments are challenging, and time is required to ensure safe and orderly evacuation.

VESDA detectors are available in a variety of models to accommodate a broad range of environments and applications. From small to very large, open spaces and from the cleanest to the dirtiest of environments, VESDA provides reliable, high-sensitivity, very early smoke detection.



The Americas +1 781 740 2223

Asia +852 2916 8894

Australia and New Zealand +61 3 9936 7000

Continental Europe +32 56 24 19 51

UK and the Middle East +44 1442 242 330

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

This document includes registered and unregistered trademarks. All trademarks displayed are the trademarks of their respective owners. Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label. This document is subject to copyright owned by Xtralis AG ("Xtralis"). You agree not to copy, communicate to the public, adapt, distribute, transfer, sell, modify or publish any contents of this document without the express prior written consent of Xtralis.

Doc. 10947_01