

# 5 ■ SOLDERING / WATERPROOFING / ROOFING

## WATERPROOFER TORCH

### 5250 : Waterproofer's Torch – X 400 Handle

General shut-off valve. Constant pilot light adjustment.  
Heat and bitumen-resistant handle. Threaded nipple for connecting straight or swivel couplings.  
Rounded handle for a good, easy grip even without gloves. Set of two interchangeable burners fitting onto single connecting tubes. All burners fitted with an adjustable stand. Long trigger for easy operation with or without gloves.  
**Tip:** Use only with propane gas.  
Operating pressure: 4 bar.



Composition	Connection "	Kg	Ref.
Swivel coupling, X 400 handle	M 16 x 1,5	0,540	525000
X 400 handle, Connecting tube 240 mm, Jet 3 burner Ø 42 mm	M 16 x 1,5	1,080	525070
X 400 handle, Connecting tube 240 mm, Jet 4 burner Ø 52 mm	M 16 x 1,5	1,080	525072
4 bar fixed pressure regulator, Waterproofer 10m straight hose, X 400 handle	M 16 x 1,5	2,130	525090

### 5250 : Burner for X 400 Handle Waterproofing Torches

Circular burner.



Description	Nozzle Ø int. Mm	Flame Ø mm	Flame L mm	Flow rate kg/h 4 bar	Energy supplied kJ/h at 4 bar	Kg	Ref.
Jet 3	42	60	600	4,1	179500	0,270	525013
Jet 4	52	90	800	7,9	347000	0,370	525014

### 5250 : Connecting Tubes for Jet Burners 3-4 for X 400 Handle Waterproofing torches

Description	L mm	Kg	Ref.
Single 31	240	0,140	525021
Single 33	350	0,190	525022
Single 34	660	0,280	525023



Go to [www.virax.com](http://www.virax.com)

To find a product sheet, a safety data sheet or exploded views,  
Go to our web site.