

SELF-PRIMING ENGINE DRIVEN PUMPS

Series: AL8M
3.5 to 6.5 HP
Suction: 2"
Discharge: 2"



SUCTION

2" NPT, horizontal, with flange.

DISCHARGE

2" NPT, horizontal.

DISCHARGE ELBOW

Aluminum. It can be rotated 90°.

BODY

Aluminum.

VOLUTE

Cast iron ASTM A-48, class 30.

BRACKET

Aluminum.

IMPELLER

Design: 3 vanes, open, statically balanced.

Material: cast iron ASTM A-48, class 30.

RETENTION VALVE

Reinforced rubber.

GASKETS

Buna-N.

SEAL

Design: mechanical, self lubrication.

Material: ceramic stationary part, carbon ring seal and exclusion in the rotating part. Buna-N elastomer and stainless steel spring.

STRAINER & HOSE ADAPTERS

Aluminum.

MOTOR

Assembled to a gasoline engine, single-cylinder, 4-stroke, air-cooled, OHV (Overhead Valve).

MOTOR	MODEL	HP	START	WEIGHT (pounds)
Briggs & Stratton	93432	3.5	Recoil	48.5
Briggs & Stratton	123432	6.5	Recoil	57.3
Honda	GX160	5.5	Recoil	52.9

ROLL FRAME

Steel.

SPECIFICATIONS

