

Capacities

Steel: BSPT, NPT Ø 1/4" - 2".
 Stainless steel: BSPT, NPT Ø 1/4" - 2".

Delivered with

- 1 automatic 1/2" to 2" BSPT and NPT threading head,
- 1 set of right-hand BSPT dies 1/2" - 3/4",
- 1 set of right-hand BSPT dies 1" - 2",
- 1 set of carbon brushes,
- 1 steel pipe cutting wheel,
- 5 L container of oil (Ref. 110605),
- 4 support legs,
- 1 safety pedal.

Tips

Use specially-designed dies and cutting wheels when working with zinc-coated and stainless steel.

1621 : Threading Machine 4"




Automatic opening threading head.
Quick, simple thread size adjustment.
Hammer-type chuck and long jaws to rapidly, firmly and safely secure the pipe.



Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

- Self-priming gear-style oil pump.
- Raised strainer avoids oil contamination by iron filings.
- Variable oil flow control.
- Heavy-duty dies available in HSS and standard grade steel.
- Slotted dies for quick and easy replacement without removing the head.
- 3 gears for optimum cutting and threading of each pipe diameter.
- Safety pedal for starting and stopping the machine.
- Three-blade reamer for a precision result.
- Special storage compartment.
- A machine of proven endurance, designed for high-volume applications, the 4" threading machine is the ideal solution for all your grooving and threading needs.



| Motor | Power W | Composition | Dies | Speed rpm | Size mm | Kg | Ref. |
|------------------------------------|---------|--|-----------------|-----------|-------------------|---------|--------|
| Single-phase induction 230 V motor | 1600 | Ø": 1/2 - 3/4, 1 - 2, 2.1/2 - 4. Ø mm: 8/13 - 12/17, 26/34 - 50/60, 66/76 - 102/114 | Right-hand BSPT | 36/20/11 | 1200 x 870 x 1200 | 142,200 | 162140 |

Capacities

Steel: BSPT, NPT Ø 1/4" - 4".
 Stainless steel: BSPT, NPT Ø 1/4"- 4".