


RUBBER FAB

technologies group

RFPSSG



Polysulfone Sight Gauge

TEMPERATURE: -20°F to 240°F

MOLDED END CONNECTIONS:

Tri-Clamp®

Maxi Tri-Clamp®

MPT - Only available in 1" (.86" ID)

Male and Female NPT x Tri-Clamp adapters are also available in both polypropylene and PVDF

Part Number	Hose ID Inch	Hose OD Inch	TC Size	Max. Working Pressure @ 70°F
08RFPSSG08TC08TCM	0.50	0.63	0.50	176 psi
12RFPSSG12TC12TCM	0.56	0.75	0.75	176 psi
16RFPSSG16TC16TCM	0.86	1.11	1" Ladish®	176 psi
16RFPSSG16MTC16MTCM	0.86	1.11	1" Maxi	125 psi
24RFPSSG24TC24TCM	1.36	1.61	1.50	125 psi
32RFPSSG32TC32TCM	1.86	2.11	2.00	125 psi
40RFPSSG40TC40TCM	2.36	2.61	2.50	62 psi
48RFPSSG48TC48TCM	2.86	3.11	3.00	62 psi
64RFPSSG64TC64TCM	3.81	4.06	4.00	44 psi

This product is factory fabricated.

Features

- Light weight
- Perfect surface connection prevents bacteria trap

Certifications

- FDA 21 CFR 177.1655