

Delivered with

- 2 Li-Ion batteries 18 V – 1.5 Ah, 1 fast charger.
- 1 mother clamp.
- Supplied in a case without insert.

2532 : Viper® P25+ Battery-Powered Hydraulic Press Fitting Machine



- Light:** Only 4 kg with the battery.
- Quick:** very short press fitting cycle (about 5 sec.), with automatic piston return.
- Practical:** 2 frontal lights to light the part to press.

Handy and effective:

Hydraulic press fitting machine 32 kN, with 360° pivoting head and automatic piston return. Lightweight and fast cycle guaranteeing effective and easy work for the user in all working conditions.

Anti-slip Soft Touch ergonomic handle

Temperature of use between -10° C and +60° C

Smart with its electronic card:

Crimping cycle end or interruption indicator

Battery charge indicator

Cycle service indicator at 20 000 cycles with early warning at 19 500.

Automatic machine shutdown to save batteries.

Safety focus:

Crimping clamps locked by a lever at 180° to prevent untimely locking

Press fitting machine locked when battery charge insufficient to make a complete cycle

The user may stop crimping at any time with the emergency stop button

Li-Ion 18V / 3 Ah battery: increased crimping time, resists to cold (down to -10°C), Soft Touch protection reinforcements, minimum auto-discharge and no memory effect.

Size (with battery): 411 x 249 x 93 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.



4

Description	Size mm	Crimping force kN	Kg	Ref.
Viper® P25+ 18V – 3Ah Li-ion	680 x 423 x 160	32-34	4,030	253261

Capacities

- Copper: Ø 12 - 54 mm.
- Stainless steel: Ø 12 - 54 mm.
- PER/PEX: Ø 12 - 32 mm.
- Multilayer: Ø 12 - 110 mm.
- Electro-zinc steel (or carbon steel): Ø 12 – 54 mm.

Delivered with

- 2 Li-ion batteries 14.4 V - 3 Ah.
- 1 fast 85 min. charger.
- Without crimping jaws.
- In a case.